


# AX17


## Atlas 17" Quad 3G-SDI/HDMI 4K Monitor



### What's Included

- 1x AX17 Monitor
- 1x Power Cable
- 1x Light Stand Mount
- 1x Rack Mount Set

# Getting Started



## Button Notes

F1 - F5 Buttons: Functions can be mapped in the menu.  
Menu Wheel/Button: Press to opens the menu options.

# Configuration of Setting Menus

## Display Settings

Brightness – 0-100  
Contrast – 0-100  
Saturation – 0-100  
Hue – 0-100  
Sharpness – 0 ; 2 ; 4  
Backlight – 0-100  
Color Temp – 9300K, 7500K, 6500K, 58000K, sRGB, User (Custom)  
Gamma – Off, 1.8, 2.0, 2.2, 2.4

## Functions

Center Mark – On, Off  
Safe Area – Off, 95, 93, 90, 88, 85, 80 (Percent)  
Display Ratio – Full, 16:9, 4:3, 5:4, 1:1, 1.85:1  
Underscan – On, Off  
Check Field – Off, Red, Green, Blue  
Freeze – On, Off  
Peaking Color – On, Off  
Battery Information – On, Off

## Display Mode

1P – Display single signal output  
2P LR – Display two signal left and right  
2P TB – Display two signal top and bottom  
2P PIP – Display two signal picture in picture  
4P – Display four signals

## Display Functions

Display Rotate – 0, 90, 180, 270 (Degrees)  
Freeze – On, Off  
L/R Ratio – Adjust L/R display ratio  
Swap – switch the two signals  
Flip-H – Flips the image horizontally

## Signal Source

SDI 1  
SDI 2  
SDI 3  
SDI 4  
HDMI 1  
HDMI 2

## Audio

Volume – 0-100  
Audio Source – Analog, Digital  
Mute – On, Off

## System

Reset – reset to factory settings  
OSD HPOS – Adjust horizontal location of menu  
OSD VPOS – Adjust vertical location of menu  
Language – English, Chinese  
Rotate – 0, 90, 270 (Degree)  
Border Width – 0-100  
Border Color – Red, Green, Blue



## Rack Mount Installation



## Light Stand Mount Installation



## Specifications

Aspect Ratio	16:9
Display Size	17"
Brightness	400 cd/m2
Contrast Ratio	1000:1
Inputs	2 x HDMI, 4 x 3G-SDI
Outputs	4 x 3G-SDI
Resolution	3840 x 2160
Shipping Dimensions	23.5 x 8.5 x 16 in.
Shipping Weight	19 lb
UPC Code	847983026005
Viewing Angle	178°(89°/89°)

## Supported Video Signals Specifications

HDMI	720x480i & 720x480p @ 59.94, 60 Hz 720x576i & 720x576p @ 50 Hz 1280x720p @ 50, 59.94, 60 Hz 1920x1080i @ 50, 59.94, 60 Hz 1920x1080psf @ 24, 25, 29.97, 30 Hz 1920x1080p @ 23.97, 24, 25, 29.94, 30, 50, 59.94, 60 Hz 3840x2160p @ 24, 25, 30 Hz 4096x2160p @ 24 Hz
SDI	720x480i @ 59.94, 60 Hz 720x576i & 720*576p @ 50 Hz 1280x720p @ 50, 60 Hz 1920x1080i @ 50, 59.94, 60 Hz 1920x1080psf @ 24, 25, 29.97, 30 Hz 1920x1080p @ 23.93, 24, 25, 29.97, 30, 50, 59.94, 60 Hz

## Optional Accessories

Some other products that work well with the AX17 available from Ikan include:

IB-HDL98S    98Wh Professional Battery (V-Mount)  
C-2KIT-98S    Dual Charger and 2x 98Wh Battery Kit (V-Mount)

## Learn More

More dynamic information at official website: [www.ikancorp.com](http://www.ikancorp.com)

## Support

Contact email: [support@ikancorp.com](mailto:support@ikancorp.com)

---

### CONDITIONS OF WARRANTY SERVICE

- Free service for one year from the day of purchase if the problem is caused by manufacturing errors.
- The components and maintenance service fee will be charged if the warranty period is expired.

Free Service will not be provided in the following situations: (\*Even if the product is still within the warranty period.)

- Damage caused by abuse or misuse, dismantling, or changes to the product not made by the company.
- Damage caused by natural disaster, abnormal voltage, and environmental factors, etc.

©2018 Ikan Corporation. All rights reserved

