

BEM-072

BEM-072 is a cost-effective 7" on-camera monitor with its own color-calibrated screen and selectable color temperatures, accepting SD through 3G SDI. A DV battery or V-Mount is attachable on the back. Single/Dual rack mount kits are available in option.

LCD			
Size	7"	Luminance of White	400 cd/m ²
Resolution	1024 x 600	Contrast	900 : 1
Pixel Pitch	0.15 x 0.15mm	Back Light	LED
Color	8bit	Display Area (H x V)	153.6 x 90.0mm
Viewing Angle	160(H), 160(V)		
Input			
3G/HD/SD-SDI	HDMI (with HDCP v.1.3), 19pin Female		
Output			
SDI Loop Through			
Input Signal Format			
SMPTE 425M AB	SMPTE 274M/292M	SMPTE 296M	SMPTE 260M
SMPTE 125M/259M	2K, SMPTE 428M	ITU R-BT.656	
Audio In/Out		Weight	
1 x Headphone Jack Out		0.8kg / 1.76lbs	

* Optional accessories available

- Pixel-to-Pixel View
- Supporting 3G-SDI (Level A/B)
- H/V Delay, RGB/Mono
- Exposure Range Check(SDI Only)
- Zero/Under/Over Scan
- Monitor Control/Update via RS-422
- Supporting parade mode
- Waveform/Vectorscope (SDI)
- 3 Color TALLY Lamp-Remote Control via GPI(RJ-45) Port
- False Color (SDI Only)
- PiP, PaP (Between SDI & HDMI Input)
- Firmware Update via USB Memory
- Copying the preset data to another monitor by USB memory
- R/G/B and White Internal Patterns Display
- V-CHIP display (SDI Only)
- Various Markers
- Focus Assistance(SDI Only)
- Time Code Display(SDI Only)
- UMD Mode Display

BEM Series BEM-072

