

BEM-072H

BEM-072H is a cost-effective 7" on-camera monitor with the luminance of 1100 cd/m². It accepts SD-SDI through 3G SDI, providing a clear view under the sunlight. A DV battery or V-Mount is attachable on the back.

LCD			
Size	7"	Luminance of White 1100 cd/m ²	
Resolution	1024 x 600	Contrast	900 : 1
Pixel Pitch	0.15 x 0.15mm	Back Light	LED
Color	8bit	Display Area (H x V) 153.6 x 90.0mm	
Viewing Angle	160(H), 160(V)		
Input			
3G/HD/SD-SDI HDMI (with HDCP v.1.3), 19pin Female			
Output			
SDI Loop Through			
Input Signal Format			
SMPTE 425M AB	SMPTE 274M/292M	SMPTE 296M	SMPTE 260M
SMPTE 125M/259M	2K, SMPTE 428M	ITU R-BT.656	
Audio In/Out			
1 x Headphone Jack In			
Weight			
0.8kg / 1.7lbs			

* Optional accessories available

- Supporting parade mode
- V-CHIP display (SDI Only)
- Focus Assistance (SDI Only)
- 2CH Audio Level Meter(HDMI)
- Time Code Display (SDI Only)
- Supporting 3G-SDI (Level A/B)
- Exposure Range Check(SDI Only)
- Waveform/Vector scope (SDI Only)

- Monitor Control/Update via RS-422
- Remote Control via GPI(RJ-45) Port
- PiP, PaP(Between SDI and HDMI Input)
- Firmware Update via USB Memory
- Closed Caption (CEA-608/708)
- UMD Mode Display
- Various Markers

Super Bright BEM-072H



- 3 Color TALLY Lamp
- Zero/Under/Over Scan
- False Color (SDI Only)
- 10-bit Signal Processor
- Battery Level Indicator