

BEM Series BEM-182

**Rack mountable
6RU Fitted in**



BEM-182

BEM-182 is a cost-effective 18.5" LED broadcast monitor with its own color-calibrated screen and selectable color temperatures. It can be attached in front of a rack, providing larger viewable area than a general 17" rack/wall mount monitor and run on V-Mount or Anton Bauer battery attachable on the back.

LCD			
Size	18.5"	Color	6 + FRC 2bit
Resolution	1366 x 768	Luminance of White	250 cd/m ²
Pixel Pitch	0.3 x 0.3mm	Back Light	LED
Viewing Angle	170(H), 160(V)	Display Area (H x V)	409.8 x 230.4 mm
Contrast	1000 : 1		
Input			
3G/HD/SD-SDI		HDMI1.3 (with HDCP v.1.3), 19pin Female	
Output			
SDI Loop Through			
Input Signal Format			
SMPTE 425M AB	SMPTE 274M/292M	SMPTE 296M	SMPTE 260M
SMPTE 125M/259M	2K, SMPTE 428M	ITU R-BT.656	HDMI
Audio In/Out			
1 x Headphone Jack Out			

* Optional accessories available

- Time Code Display(SDI Only)
- H/V Delay, RGB/Mono (SDI ONLY)
- Exposure Range Check(SDI Only)
- Monitor Control/Update via RS-422
- PiP/PaP (Between SDI & HDMI Input)
- Closed Caption(CEA-608/708,SDI only)
- Pixel to Pixel
- UMD Mode Display
- 3 Color TALLY Lamp
- Zero/Under/Over Scan
- Supporting parade mode
- Remote Control via GPI(RJ-45) Port
- V-CHIP display (SDI Only)
- Waveform/Vectorscope (SDI)
- Focus Assistance(SDI Only)
- Firmware Update via USB Flash Memory
- 10-bit Signal Processor
- False Color (SDI Only)
- Various Markers