

BEM-212

BEM-212 is a cost-effective 21.5" LED broadcast monitor. It has a color-calibrated screen with selectable color temperatures. A V-Mount or Anton Bauer battery is attachable on the back.

LCD			
Size	21.5"	Color	8bit
Resolution	1920 x 1080	Luminance of White	250 cd/m ²
Pixel Pitch	0.24825mm	Back Light	LED
Viewing Angle	178(H),178(V)	Display Area (H x V)	476.64 x 268.11 mm
Contrast	3000:1		
Input			
3G/HD/SD-SDI	HDMI, (with HDCP v.1.1), 19pin Female		
Output			
SDI Loop Through			
Input Signal Format			
SMPTE 425M AB	SMPTE 274M/292M	SMPTE 296M	SMPTE 260M
SMPTE 125M/259M	2K, SMPTE 428M	ITU R-BT.656	HDMI
Audio In/Out			
1 x Headphone Jack Out			

* Optional accessories available

- Various Markers
- Supporting 3G-SDI (Level A/B)
- UMD Mode Display
- Exposure Range Check(SDI Only)
- Time Code Display
- Waveform/Vectorscope (SDI Only)
- Remote Control via GPI(RJ-45) Port

- 10-bit Signal Processor
- V-CHIP display (SDI Only)
- H/V Delay, RGB/Mono, Pixel to Pixel
- Firmware Update via USB Memory
- Focus Assistance(SDI Only)
- R/G/B and White Internal Patterns Display(SDI Only)
- Copying the preset data to another monitor by USB memory
- 3 Color TALLY Lamp
- Monitor Control/Update via RS-422
- Zero/Under/Over Scan
- PiP/PaP (Between SDI & HDMI Input)
- False Color (SDI Only)
- Closed Caption(CEA-608/708)

BEM Series BEM-212

