

BQM-240LS

LCD			
Size	24"	Luminance of White	400 cd/m ²
Resolution	1920 x 1200	Contrast	1000 : 1
Pixel Pitch	0.270mm	Back Light	CCFL
Color	8bit	Display Area (H x V)	518.4 x 324.0 mm
Viewing Angle	178(H), 178(V)		
Input			
SDI Input	Analog Input	DVI Input	PC-RGB(DVI) Input
HDMI Input	S-Video Input		
Output			
SDI Loop Output			
Analog Input Level			
Composite	YC(S-Video)	Component(Y/Pb/Pr)	
Component (R/G/B)		PC-RGB,Sync Level	
Input Signal Format			
SMPTE 274M/292M	SMPTE 296M	SMPTE 260M	SMPTE 259M/125M
2K, SMPTE 428M	ITU R-BT.656	HDMI Digital	DVI Digital
Component			
PC-RGB(DVI) Mode			
Audio In/Out			
1 x Line In	1 x Line Out	2 x Speaker Out	

* Optional accessories available

- HD SDI Signal Reception
- 2 Assignable Function Keys
- Current Time Clock Display
- Closed Caption (CEA 608, 708)
- Advanced Video Analysis Features

- Various Markers
- Pixel-to-Pixel View
- Waveform/Vectorscope
- 16Ch Audio Level(H/V)
- Various Input Signals
- Various Split Screens

Quad Series BQM-240LS

BQM-240LS splits and displays up to 4 different video inputs on the screen by user selectable input display.

