

BSM-153H

BSM-153H is a 15" super bright monitor with 3G SDI and advanced peaking features. It can be easily installed or uninstalled on a rack or a jib plate.

*A program monitor can be attached onto it by using one of three holes at the top.

LCD			
Size	15"	Luminance of White	1500 cd/m ²
Resolution	1024 x 768	Contrast	700 : 1
Pixel Pitch	0.297 mm	Back Light	LED
Color	8bit	Display Area (H x V)	304.13 x 228.10 mm
		Viewing Angle(deg)	160(H), 160(V)
Input			
3G/HD/SD-SDI	Analog(YPbPr/CVBS/S-Video/RGB)		DVI-I, 24pin, Female
HDMI (with HDCP v.1.1), 19pin Female	DVI-I to VGA Jack (with gender)		
Output			
SDI-1/2 Active Loop Output	Analog(YPbPr/CVBS/S-Video/RGB)		
Analog Input Level			
Composite	YC(S-Video)	Component(Y/Pb/Pr)	
Component (R/G/B)	PC-RGB,Sync Level		
Input Signal Format			
SMPTE 425M AB	2K, SMPTE 428M	SMPTE 274M/292M	SMPTE 296M
SMPTE 260M	SMPTE 125M/259M	ITU R-BT.656	Composite
Component, VGA	DVI Signal	HDMI Digital	
Audio In / Out			
1 x Headphone Jack In	2 x Headphone Jack Out	2 x Speaker Out	
Weight			
5kg/11lbs			

* Optional accessories available

- R/G/B and White Internal Patterns Display
- Copying the preset data to another monitor by USB Memory
- PiP/PaP (Between SDI & HDMI Input)
- Zero/Under/Over Scan

Jimmy Jib Mountable Super Bright

Best Rated

BSM-153H



- 10bit Signal Processor
- Focus Assistance
- Closed Caption (CEA-608/708)
- Exposure Range Check
- Various Markers
- Remote Control via GPI(RJ-45) Port
- AFD & V-CHIP(SDI Only)
- 3 Mount Halls on Top
- Firmware Update via USB Memory
- 3G-SDI (Level A/B)
- Time Code
- H/V Delay, Blue/Mono, Pixel to Pixel
- Supporting 3G-SDI (Level A/B)
- UMD/IMD Mode
- Update/Control via RS-422 or Ethernet
- Waveform/Vecor Scope
- False Color
- 8~16ch Audio Level Meter