

BSM-213H

Weighting only 12.2lbs, BSM-213H is a 21.5" super bright monitor with the resolution of 1920x1080 and luminance of 1200 cd/m². Suitable for both outdoor shooting and studio monitoring, it is now lighter and smaller in volume than a general 21" broadcast monitor.

LCD			
Size	21.5"	Luminance of White	1200 cd/m ²
Resolution	1920 x 1080	Back Light	LED
Pixel Pitch	0.248,25mm	Display Area (H x V)	476.64 x 268.11mm
Color	8bit	Viewing Angle(deg)	178(H), 178(V)
Contrast	3000 : 1		
Input			
HD/SD-SDI	Analog(YPbPr/CVBS/S-Video/RGB)		DVI-I, 24pin, Female
HDMI (with HDCP v.1.1), 19pin Female	DVI-I to VGA Jack (with gender)		
Output			
SDI-1/2 Active Loop Output	Analog(YPbPr/CVBS/S-Video/RGB)		
Analog Input Level			
Composite	YC(S-Video)	Component(Y/Pb/Pr)	
Component (R/G/B)	PC-RGB,Sync Level		
Input Signal Format			
SMPTE 425M AB	2K, SMPTE 428M	SMPTE 274M/292M	SMPTE 296M
SMPTE 260M	SMPTE 125M/259M	ITU R-BT.656	Composite
Component, VGA	DVI Signal	HDMI Digital	
Audio In / Out			
1 x Headphone Jack In	2 x Headphone Jack Out	2 x Speaker Out	
Weight			
6kg/12.2lbs			

* Optional accessories available

- Supporting 3G-SDI (Level A/B)
- Monitor Control/Update via Ethernet/RS-422
- Copying the preset data to another monitor by USB memory
- Firmware Update via USB Memory

FULL HD Super Bright BSM-213H



- PiP, PaP(Between analog and digital input)
- 10bit Signal Processor
- Waveform / Vector scope
- Closed Caption (CEA-608/708, SDI Only)
- Time Code Display (ATC_HD-SDI,DVITC_SD-SDI)
- Exposure Range Check
- AFD & V-CHIP display (SDI Only)
- Various Markers (EBU, 4:3, 16:9, 1.85:1, 2.35:1, etc.)
- H/V Delay, Blue/Mono, Pixel to Pixel
- Zero/Under/Over Scan
- Remote Control via GPI(RJ-45) port
- False Color (SDI Only)
- Freeze Frame
- Focus Assistance
- UMD/IMD Mode Display
- 3 Color Tally Lamp