

# BSM Series

## BSM-173N3G



- Exposure Range Check
- Zero/Under/Over Scan
- AFD /V-CHIP(SDI Only)
- 8~16ch Audio Level Meter
- Focus Assistance
- R/G/B or Gray Only Display
- R/G/B and White Internal Pattern Display

- Time Code Display
- False Color
- UMD/IMD Mode
- Freeze Frame
- Tally Display
- Various Markers
- Copying the preset data to another monitor by USB Memory

- 3G SDI (Level A/B)
- Monitor Controllable via Ethernet
- PiP/PaP (Between SDI & HDMI Input)
- H/V Delay
- Pixel-to-Pixel View
- Closed Caption(CEA-608/708)

\* Optional accessories available

## BSM-173N3G

BSM-173N3G, a 17" broadcast monitor with its native full HD screen accepts 3G SD signals.

LCD			
Size	17.3"	Pixel Pitch	0.1989 x 0.1989 mm
Resolution	1920 x 1080	Color	6 + FRC 2bit
Viewing Angle	160(H), 140(V)	Luminance of White	400 cd/m <sup>2</sup>
Contrast	600 : 1	Display Area (H x V)	381.88 x 214.81 mm
Back Light	LED		
Input			
3G/HD/SD-SDI	Analog(YPbPr/CVBS/S-Video/RGB)	DVI-I, 24pin, Female	
HDMI (with HDCP v.1.1), 19pin Female		DVI-I to VGA Jack (with gender)	
Output			
SDI-1/2 Active Loop Output	Analog(YPbPr/CVBS/S-Video/RGB)		
Input Signal Format			
SMPTE 260M	SMPTE 125M/259M	ITU R-BT.656	Composite
Component, VGA	DVI Signal	HDMI Digital	SMPTE 425M AB
2K, SMPTE 428M	SMPTE 274M/292M	SMPTE 296M	
Analog Input Level			
Composite	YC(S-Video)	Component(Y/Pb/Pr)	Component (R/G/B)
PC-RGB, Sync Level			
Audio In/Out			
1 x Headphone Jack In	2 x Headphone Jack Out	2 x Speaker Out	