

Jimmy Jib Mountable Super Bright **BSM-183H**



- Firmware Update via USB Memory
- 2 Hand Grips on Top and Left side
- Remote Control via GPI(RJ-45) Port
- H/V Delay, Blue/Mono, Pixel to Pixel
- Update/Control via RS-422 or Ethernet
- R/G/B and White Internal Patterns Display
- 10bit Signal Processor
- Copying the preset data to another monitor by USB Memory

Being lighter and smaller in volume than a general 17" broadcast monitor, BSM-183H is an 18.5" super bright monitor suitable for outdoor shooting. BSM-213H is available for a larger full HD display (21.5")

LCD			
Size	18.5"	Color	6 + FRC 2bit
Resolution	1368 x 768	Luminance of White	1200 cd/m ²
Pixel Pitch	0.3 mm	Back Light	LED
Viewing Angle	170(H), 160(V)	Display Area (H x V)	409.8 x 230.4 mm
Contrast	1000 : 1		
Input			
3G/HD/SD-SDI		Analog(YPbPr/CVBS/S-Video/RGB)	DVI-I, 24pin, Female
HDMI (with HDCP v.1.1), 19pin Female		DVI to VGA Jack (with gender)	
Output			
SDI-1/2 Active Loop Output		Analog(YPbPr/CVBS/S-Video/RGB)	
External Sync			
Input Signal Format			
SMPTE 425M AB	SMPTE 372M	SMPTE 274M/292M	SMPTE 296M
SMPTE 260M	SMPTE 125M/259M	2K, SMPTE 428M	Composite
Component, VGA	DVI Signal	HDMI Digital	
Analog Input Level			
Composite	YC(S-Video)	Component(Y/Pb/Pr)	Component (R/G/B)
PC-RGB,Sync Level			
Audio In/Out			
1 x Headphone Jack In		2 x Headphone Jack Out	2 x Speaker Out
Weight			
5.5kg / 12.2lbs			

* Optional accessories available

- | | | |
|--------------------------------|--------------------|-----------------------|
| ·AFD & V-CHIP(SDI Only) | ·False Color | ·3 Color TALLY Lamp |
| ·8~16ch Audio Level Meter | ·UMD/IMD Mode | ·3G-SDI (Level A/B) |
| ·Closed Caption (CEA-608/708) | ·Various Markers | ·Exposure Range Check |
| ·Supporting 3G-SDI (Level A/B) | ·Focus Assistance | ·Waveform/Vecor Scope |
| | ·Time Code Display | ·Zero/Under/Over Scan |