

BSM-212i

BSM-212i is a 21.5" professional broadcast monitor with a 10-bit video processor. Its full HD 1920x1080 resolution achieves the best image quality for monitoring by providing sharp 1:1 mapped pixels.

LCD			
Size	21.5"	Luminance of White	250cd/m ²
Resolution	1920 x 1080	Contrast	3000 : 1
Color	8bit	Pixel Pitch	0.24825 mm
Viewing Angle	178(H), 178(V)	Display Area (H x V)	476.64 x 268.11 mm
Back Light	LED		
Input			
HD/SD-SDI	Analog(YPbPr/CVBS/S-Video/RGB)	DVI-I, 24pin, Female	
HDMI (with HDCP v.1.1), 19pin Female		DVI-I to VGA Jack (with gender)	
Output			
SDI-1/2 Active Loop Output		Analog(YPbPr/CVBS/S-Video/RGB)	
Input Signal Format			
SMPTE 274M/292M	SMPTE 296M	SMPTE 260M	DVI
SMPTE 125M/259M	2K, SMPTE 428M	ITU R-BT.656	HDMI
Audio In/Out			
1 xHeadphone Jack In	2 x Headphone Jack Out	2 x Speaker Out	

* Optional accessories available

- 10bit Signal Processor
- AFD & V-CHIP(SDI Only)
- Waveform/Vector Scope
- Update/Control via RS-422
- UMD/IMD Mode
- Firmware Update via USB Memory
- H/V Delay
- Time Code
- False Color
- Freeze Frame
- Various Markers
- 1920x1080 Full HD Resolution
- Closed Caption (CEA-608/708)
- Remote Control GPI(RJ-45) port
- Zero/Under/Over Scan/Zoom Scan
- PiP/PaP (Between HDMI & SDI Input)
- Copying the preset data to another monitor by USB memory
- Focus Assistance
- R,G,B and Gray only Display
- 3 Color Tally Lamp
- Pixel-to-Pixel View
- Exposure Range Check

BSM i Series BSM-212i

