

# BSM Series

## BSM-213N3G



## BSM-213N3G

BSM-213N3G, a 21.5" broadcast monitor with 3G SDI signals reproduces high quality pictures with a wide color range and smooth gradient.

LCD			
Size	21.5"	Luminance of White	250 cd/m <sup>2</sup>
Resolution	1920 x 1080	Contrast	1000 : 1
Pixel Pitch	0.24795mm	Back Light	LED
Color	6 + FRC 2bit	Display Area (H x V)	476.064 x 267.768 mm
Viewing Angle	178(H), 178(V)		
Input			
3G/HD/SD-SDI	Analog(YPbPr/CVBS/S-Video/RGB)	DVH, 24pin, Female	
HDMI (with HDCP v.1.1), 19pin Female		DVH to VGA Jack (with gender)	
Output			
SDI-1/2 Active Loop Output	Analog(YPbPr/CVBS/S-Video/RGB)		
Input Signal Format			
SMPTE 260M	SMPTE 125M/259M	ITU R-BT.656	Composite
Component, VGA	DVI Signal	HDMI Digital	SMPTE 425M AB
2K, SMPTE 428M	SMPTE 274M/292M	SMPTE 296M	
Analog Input Level			
Composite	YC(S-Video)	Component(Y/Pb/Pr)	Component (R/G/B)
PC-RGB, Sync Level			
Audio In/Out			
1 x Headphone Jack In	2 x Headphone Jack Out	2 x Speaker Out	

\* Optional accessories available

- Zero/Under/Over Scan
- Time Code
- Waveform/Vector Scope
- False Color
- 10bit Signal Processor
- UMD/IMD Mode
- AFD & V-CHIP(SDI Only)
- Remote Control via GPI(RJ-45) Port

- Freeze Frame
- 3G-SDI (Level A/B)
- PiP/PaP (Betweent SDI & HDMI Input)
- 3 Color TALLY Lamp
- H/V Delay, Blue/Mono, Pixel to Pixel
- Exposure Range Check
- Update/Control via RS-422 or Ethernet
- Copying the preset data to another monitor by USB memory

- Closed Caption (CEA-608/708)
- Various Markers
- R/G/B and Gray only Display
- Focus Assistance