

BXM-323L3G

LCD			
Size	31.5"	Luminance of White	350 cd/m ²
Resolution	1920 x 1080	Contrast	3000 : 1
Pixel Pitch	0.36375mm	Back Light	LED
Color	8bit	Display Area (H x V)	698.4 x 392.8mm
Viewing Angle	178(H), 178(V)		
Input			
3G/HD/SD-SDI	Analog(YPbPr/CVBS/S-Video/RGB)		
HDMI (with HDCP v.1.1), 19pin Female	External Sync, Black Burst & Tri-sync, 1.0Vp-p		
DVI-I, 24pin, Female	DVI to VGA Jack (with gender)		
Output			
SDI-1/2 Active Loop Output	Analog(YPbPr/CVBS/S-Video/RGB)		
External Sync			
Input Signal Format			
SMPTE 425M AB	SMPTE 372M	SMPTE 274M/292M	SMPTE 296M
SMPTE 260M	SMPTE 125M/259M	2K, SMPTE 428M	
ITU R-BT.656	HDMI	DVI	
Analog Input Level			
Composite	YC(S-Video)	Component(Y/Pb/Pr)	Component (R/G/B)
PC-RGB,Sync Level			
Audio In/Out			
1 x Headphone Jack In	2 x Headphone Jack Out	2 x Speaker Out	

* Optional accessories available

- 12bit Signal Processor
- 3 Color TALLY Lamp
- 3G-SDI (Level A/B)
- AFD & V-CHIP(SDI Only)
- Blending, PaP, PiP
- Firmware Update via USB Memory

- Closed Caption (CEA-608/708)
- Exposure Range Check
- False Color
- Fast Motion Mode
- Blue/Mono

- Update/Control via RS-422 or Ethernet
- Gen-Lock(video synchronization)
- H/V Delay
- I/P Conversion for Motion Response
- Pixel-to-Pixel View
- Remote Control via GPI(RJ-45) Port

- Time Code
- UMD/IMD Mode
- Focus Assistance
- Various Markers
- Waveform/Vector Scope
- Zero/Under/Over Scan
- Freeze Frame

BXM Series BXM-323L3G

BXM-323L3G is a high-end broadcast monitor for professionals with 12 bit video processing. Its 32" screen provides a large, comfortable monitoring area for the user, with the advanced video monitoring features.

