

BSM Series BSM-463N3G

BSM-463N3G, a 46" broadcast monitor with 3G SDI signals reproduces high quality pictures with a wide color range and smooth gradient.



- Various Markers
- Waveform/ Vector Scope
- 10-bit Signal Processor
- Supporting 3G-SDI (Level A/B)
- AFD & V-CHIP display (SDI Only)
- Remote Control via GPI(RJ-45) Port
- Copying the preset data to another monitor by USB memory
- Time Code Display
- Focus Assistance
- Control/Update via Ethernet/RS-422
- H/V Delay, Blue/Mono, Pixel to Pixel
- Firmware Update via USB Memory
- PiP, PaP(Between analog and digital input)

- 3 Color TALLY Lamp
- Zero/Under/Over Scan
- UMD/IMD Mode Display
- Exposure Range Check
- False Color (SDI Only)
- Closed Caption(CEA-608/708)

BSM-463N3G

LCD			
Size	46"	Color	6 + FRC 2bit
Resolution	1920 x 1080	Luminance of White	500 cd/m ²
Pixel Pitch	0.53 mm	Back Light	LED
Viewing Angle	178(H), 178(V)	Display Area (H x V)	1018.08 x 572.67 mm
Contrast	4000:1		
Input			
3G/HD/SD-SDI		Analog(YPbPr/CVBS/S-Video/RGB)	DVI-I, 24pin, Female
HDMI (with HDCP v.1.1), 19pin Female		DVI-I to VGA Jack (with gender)	
Output			
SDI-1/2 Active Loop Output		Analog(YPbPr/CVBS/S-Video/RGB)	
Input Signal Format			
SMPTE 260M	SMPTE 125M/259M	ITU R-BT.656	Composite
Component, VGA	DVI Signal	HDMI Digital	SMPTE 425M AB
2K, SMPTE 428M	SMPTE 274M/292M	SMPTE 296M	
Analog Input Level			
Composite	YC(S-Video)	Component(Y/Pb/Pr)	Component (R/G/B)
PC-RGB,Sync Level			
Audio In/Out			
1 x Headphone Jack In		2 x Headphone Jack Out	2 x Speaker Out

* Optional accessories available