

BXM-173T3G

Featuring a 17" Full-HD LED-backlit LCD panel with 10 bit of color depth, BXM-173T3G provides 12 bit signal processing and color space selectable Gamma selection.

LCD			
Size	17.3"	Luminance of White	300 cd/m ²
Resolution	1920 x 1080	Contrast	800 : 1
Pixel Pitch	0.199mm	Back Light	LED
Color	10bit	Display Area (H x V)	381.9 x 214.8 mm
Viewing Angle	178(H), 178(V)		
Input			
3G/HD/SD-SDI	Analog(YPbPr/CVBS/S-Video/RGB)		
DVI-I 24pin Female	External Sync Black Burst & Tri-sync 1.0Vp-p		
HDMI(with HDCP v.1.1)	19pin Female		
Output			
SDI-1/2 Active Loop Output	Analog(YPbPr/CVBS/S-Video/RGB)		
External Sync			
Analog Input			
Composite	YC(S-Video)	Component(Y/Pb/Pr)	Component (R/G/B)
PC-RGB,Sync Level			
Input Signal Format			
SMPTE 425M AB	SMPTE 372M	SMPTE 274M / 292M	SMPTE 296M
SMPTE 260M	SMPTE 125M/259M	2K, SMPTE 428M	ITU R-BT.656
HDMI	DVI		
Audio In / Out			
1 x Headphone Jack In	2 x Headphone Jack Out	2 x Speaker Out	

* Optional accessories available

- Time Code Display (ATC_HD-SDI,DVITC_SD-SDI, Except 3G Level B)
- Monitor Control/Update via Ethernet/RS-422
- I/P Conversion for Motion Response (Minimizing the delay)

3D LUT

10bit LCD

BXM-173T3G



- 12-bit Signal Processor
- False Color (SDI Only)
- Zero/Under/Over Scan
- Blending, PaP, PiP
- 3 Color Tally Lamp
- Waveform / Vector scope
- Closed Caption (CEA-608/708)
- Focus Assistance
- Exposure Range Check
- Freeze Frame
- Fast Motion Mode
- Supporting 3G-SDI (Level A/B)