

# D12-FK

D12 HDMI/3G-SDI Monitor Field Kit for V-Mount & Gold-Mount with Hard Case

ONE SHEET

## Overview

Our customer favorite, the D12, is now available in a Field Kit. The field kit integrates a D12 into a durable hard case with a sunhood, screen protector, V-Mount battery plate, Gold Mount battery plate, and stand adapter. The kit allows for handy transport, and the aluminum stand mount allows for easy placement and viewing in the field.



D12-FK | D12 HDMI/3G-SDI Monitor Field Kit for V-Mount & Gold Mount w/ Hard Case | **UPC Code:** 847983019236

## Special Features

- Resolution of 1920 x 1080
- Integrated into Hard Case for Portability
- Includes Adjustable Stand Mount, Sunhood, V-Mount Battery Plate, & Screen Protector
- 3G-SDI & HDMI Inputs and Outputs

## Recommended For

- Field Production
- Studio Use

 [www.facebook.com/ikanseit](http://www.facebook.com/ikanseit)

 [www.twitter.com/ikancorp](http://www.twitter.com/ikancorp)

 [www.vimeo.com/ikancorp](http://www.vimeo.com/ikancorp)

 [www.youtube.com/ikancorp](http://www.youtube.com/ikancorp)

# ikan

[www.ikancorp.com](http://www.ikancorp.com)

1.713.272.8822

[sales@ikancorp.com](mailto:sales@ikancorp.com)

# D12-FK

Features you need, Prices you want.

## Durable Hard Case

The D12 is integrated directly into the hard case. The hard case features a front door as well as rear door for quickly accessing all the monitor's functions. The front door also holds the sunhood in place while the rear door holds the AC adapter when not in use.

## Aluminum Adjustable Stand Mount

Included in the kit is an adjustable stand mount that is preattached to the monitor. Rosettes on the fully aluminum stand mount provide both strong support and adjustability for the monitor. Once the monitor is set at the desired angle, it can be locked into position by tightening the rosettes.

## Tools You Need

The field kit includes a four-sided sunhood that folds up and stores in the front door of the case. The hood easily attaches to the monitor with magnets. A V-Mount battery plate is pre-attached and ready to power your monitor.

## The Main Attraction

The heart of the field kit is the acclaimed D12 monitor. With its super-sharp, full HD panel you always get the best image. The panel also features IPS technology, ensuring the best viewing angles & true-to-life color reproduction.

## What's Included

- 1 x D12 Monitor w/ Built-In Hard Case
- 1 x AC Adapter
- 1 x Sunhood
- 1 x Screen Protector
- 1 x Gold Mount Plate
- 1 x V-Mount Plate (*Attached*)
- 1 x Adjustable Stand Mount (*Attached*)

| Specifications        |                                    |
|-----------------------|------------------------------------|
| Aspect Ratio          | 16:9                               |
| Brightness            | 350 cd/m2                          |
| Build Material        | Steel                              |
| Built-In Speaker      | 2Wx2                               |
| Color System          | PAL / NTSC / SECAM (Auto-Detected) |
| Contrast Ratio        | 700:1                              |
| Dimensions            | 10 x 13 x 7 In.                    |
| Display Technology    | IPS                                |
| Input Voltage         | DC 7V-24V                          |
| Inputs                | 3G-SDI, HDMI                       |
| Operating Temperature | 0°C~50°C (32°F~122°F)              |
| Outputs               | 3G-SDI, HDMI                       |
| Pixel Pitch           | 0.1335 x 0.1335                    |
| Power Consumption     | 16W                                |
| Resolution            | 1920 x 1080                        |
| Response Time         | 25ms                               |
| Screen Size           | 11.6 In.                           |
| Viewing Angle         | H: 178° / V: 178°                  |
| Weight                | 12.5 lbs                           |

| Shipping Specifications |                 |
|-------------------------|-----------------|
| Shipping Dimensions     | 14 x 10 x 8 In. |
| Shipping Weight         | 13 lbs          |

| Supported Video Signals |   |
|-------------------------|---|
| 3G-SDI                  | 1920 x 1080p @ 50, 59.94, 60 Hz                           |
|                         | 1280 x 720p @ 50, 59.94, 60 Hz                            |
| HD-SDI                  | 1920 x 1080i @ 50, 59.94, 60 Hz                           |
|                         | 1920 x 1080psf @ 23.98, 24, 25, 29.97, 30 Hz              |
|                         | 1920 x 1080psf @ 23.97, 24, 25, 29.94, 30 Hz              |
| SD-SDI                  | 720 x 480i @ 60 Hz  |
|                         | 720 x 576i @ 50 Hz  |
| HDMI                    | 720 x 480i & 720x 480p @ 59.94, 60 Hz                     |
|                         | 720 x 480i & 720 x 576i @ 50 Hz                           |
|                         | 1280 x 720p @ 50, 59.94, 60 Hz                            |
|                         | 1920 x 1080i @ 50, 59.94, 60 Hz                           |
|                         | 1920 x 1080psf @ 24, 25, 29.97, 30 Hz                     |
|                         | 1920 x 1080p @ 23.97, 24, 25, 29.94, 30, 50, 59.94, 60 Hz |

