

EG06A2

2 Stage Aluminum Tripod w/ GH06 Head (E-Image)

ONE SHEET

Overview

The EG06A2's features includes the E-Image Mono-Lock leg design and the Easy Lock base plate system delivering fast, reliable performance that rises above competitors in its price range and class.

The EG06A2 supports a payload weighing up to 13 pounds. The GA752 tripod is made of lightweight aluminum, has a 75mm bowl, and the legs are a twin tube design with two stages. The Mono-Lock feature allows for quick height adjustments of both stages with one twist. The EG06A2 extends to a maximum height of 72" and a minimum height of 32.25". An adjustable mid-level spreader provides extra security and stability.



EG06A2 | 2 Stage Aluminum Tripod w/ GH06 Head | UPC Code: 847983009763

Special Features

- Supports 13lbs 6kg | 75mm ball level feature | Height Range 32.25" to 72"
- Easy Lock Baseplate
- 2 Stage Leg Design with Mono-Lock
- 0-3 Drag Adjustment Settings | 0-5 Counter Balance Settings
- 1/4"- 20 Threaded Accessory Socket for Monitor Arm
- Separate Pan/Tilt Locks
- Mid-Level Adjustable Spreader
- Spirit Level
- Heavy Duty Padded Bag with Shoulder Strap

Recommended For

- Studio or Location Use
- Professional Cinematography
- Professional Photography
- Support Sliders, Jibs, and Gear



www.facebook.com/ikanseeit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

ikan

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com

EG06A2

Features you need, Prices you want.

Mono-Lock

The Mono-Lock feature allows for quick and easy adjustments to the height of the tripod. The user can easily change leg stages without the hassle of multiple locks.

Easy-Lock Baseplate

Attach the quick release plate in two ways; by snapping the plate from the top, or by sliding the camera plate from the rear.

Monitor Mounting Points

Attaching your monitor has never been easier; with mounting points directly on the head of the tripod you can easily see your monitor no matter how you may need to move the camera while shooting.

What's Included

- 1 x GH06 Head
- 1 x GA752 Aluminum Tripod Legs
- 1 x GB1 Tripod Pan Tilt Handle
- 1 x GS01 Mid-level Spreader
- 1 x F3 Rubber Feet
- 1 x SC1 Tripod Bag

Optional Accessories

- EI-7004** Tripod Dolly
- EI7500** Hi-Hat w/ 75/100mm Bowl
- IK-RSR6** 6" Hi-Hat Riser
- IK-RSRS** 6" Camera Riser Hi-Hat w/ Swivel
- GB3** Handle for GH15/25 Heavy Duty Heads
- MA211-R** 11" Articulating Arm w/ Single Rod Mount
- MA207** 7" Articulating Arm
- MA211** 11" Articulating Arm

Specifications

Bowl Size	75mm
Bubble Level	Standard
Build Material	Aluminum
Camera Plate Size	120 x 45 x 11mm
Camera Plate System	Sliding Base w/ Safety Locks Easy-Lock Quick-Action Top Mount
Counterbalance Settings	0-5
Pan Drag Settings	0-3
Tilt Drag Settings	0-3
Counterbalance System	Stepped
Head Load Capacity	13 lbs
Head Mount/Base	75mm Ball
Head Weight	3.5 lbs
Height Range	32.25" - 72"
Leg Payload Capacity	13 lbs
Max Height Spreader Closed	72"
Max Height Spreader Open	67"
Min Height Spreader Open	32.25"
Min Height Spreader Closed	34.5"
Pan Handle Style	Telescoping Length 355mm
Pan Lock	Thumb Lock
Shipping Dimensions	40.5" x 9.5" x 9.5"
Shipping Weight	20 lbs
Temperature Range	-40°C ~ +80°C
Tilt Lock	Thumb Lock
Tilt Range	-60°C ~ +90°C
Transport Length	34.5"

