

EG06C2

2 Stage Carbon Fiber Tripod w/ GH06 Fluid Head (E-Image)

ONE SHEET

Overview

The EG06C2's features includes the E-Image Mono-Lock leg design and the Easy Lock base plate system delivering fast, reliable performance that rises above competitors in its price range and class.

The Kit supports a payload weighing up to 13 pounds. The GC752 tripod is made of lightweight carbon fiber, has a 75mm bowl, and the legs are a twin tube design with two stages. The Mono-Lock feature allows for quick height adjustments of both stages with one twist. The EG06C2 extends to a maximum height of 72 inches and a minimum height of 32.25 inches. An adjustable mid-level spreader provides extra security and stability.



EG06C2 | 2 Stage Carbon Fiber Tripod w/ GH06 Fluid Head (E-Image) | UPC Code: 847983012077

Special Features

- Supports 13lbs 6kg | 75mm ball level feature
- 2 Stage Leg Design with Mono-Lock
- Height Range 32.25" to 72"
- 0-3 Drag Adjustment Settings | 0-5 Counter Balance Settings
- ¼"- 20 Threaded Accessory Socket for Monitor Arm
- Separate Pan/Tilt Locks
- Mid-Level Adjustable Spreader
- Spirit Level
- Heavy Duty Padded Bag with Shoulder Strap

Recommended For

- Studio or Location Use
- Professional Cinematography
- Professional Photography
- Support Sliders, Jibs, and Gear



www.facebook.com/ikanseeit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

ikan

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com

EG06C2

Features you need, Prices you want.

Mono-Lock

The Mono-Lock feature allows for quick and easy adjustments to the height of the tripod. The user can easily change leg stages without the hassle of multiple locks.

Monitor Mounting Points

Attaching your monitor has never been easier; with mounting points directly on the head of the tripod you can easily see your monitor no matter how you may need to move the camera while shooting.

Bubble Level

The head incorporates an illuminated bubble level you assist as the user sets up for any kind of shoot.

What's Included

- 1 x GC752 Carbon Fiber Tripod Legs
- 1 x GH06 Head
- 1 x F3 Rubber Feet
- 1 x GB2 Pan Handle
- 1 x GP1 Base Plate
- 1 x GS01 Mid-level Spreader
- 1 x SC1 Tripod Bag

Optional Accessories

- EI-7004 Tripod Dolly
- EI7500 Hi-Hat w/ 75/100mm Bowl
- IK-RSR6 6" Hi-Hat Riser
- IK-RSRS 6" Camera Riser Hi-Hat w/ Swivel
- GB3 Handle for GH15/25 Heavy Duty Heads
- MA211-R 11" Articulating Arm w/ Single Rod Mount
- MA207 7" Articulating Arm
- MA211 11" Articulating Arm

Specifications

Bowl Size	75mm
Build Material	Carbon Fiber
Camera Plate Size	120 x 45 x 11mm
Camera Plate System	Sliding Base Plate w/ Safety Locks
Counterbalance Settings	0-5
Pan Drag Settings	0-3
Tilt Drag Settings	0-3
Head Mount/Base	75mm Ball
Head Weight	3.5 lbs
Height Range	30 In. - 67 In.
Leg Payload Capacity	13 lbs
Max Height Spreader Closed	67 In.
Max Height Spreader Open	61 In.
Min Height Spreader Open	30 In.
Min Height Spreader Closed	34.5 In.
Pan Handle Style	Telescoping Length 355 mm
Pan Lock	Thumb Lock
Shipping Dimensions	40.5" x 9.5" x 9.5"
Shipping Weight	18 lbs
Temperature Range	-40°C ~ +80°C
Tilt Lock	Thumb Lock
Tilt Range	-60°C ~ +90°C
Transport Length	34.5 In.

