

EG10A2

2 Stage Aluminum Tripod w/ GH10 Head (E-Image)

ONE SHEET

Overview

The EG10A2's features includes the E-Image Mono-Lock design, and a 7 step counterbalance that delivers reliable performance that rises above competitors in its price range and class.

The Kit supports a payload weighing up to 22 pounds. The GA752 tripod is made of lightweight aluminum, has a 75mm bowl, and the legs are a twin tube design with two stages. The Mono-Lock feature allows for quick height adjustments of both stages with one twist. The EG10A2 extends to a maximum height of 72.5" and a minimum height of 32.25". An adjustable mid-level spreader provides extra security and stability.



EG10A2 | 2 Stage Aluminum Tripod w/ GH10 Head (E-Image) | UPC Code: 847983009770

Special Features

- Supports 22lbs 10kgs | 75mm ball
- 2 Stage Leg Design with Mono-Lock
- Height Range 32.25" to 72.5"
- 0-3 Drag Adjustment Settings | 1-7 Counter Balance Settings
- ¼"-20 Accessory Socket for Monitor Arm
- Separate Pan/Tilt Locks
- Mid-Level Spreader
- Illuminated Spirit Level
- Heavy Duty Padded Bag with Shoulder Strap

Recommended For

- Studio or Location Use
- Professional Cinematography
- Professional Photography
- Support Sliders, Jibs, and Gear



www.facebook.com/ikanseeit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

ikan

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com

EG10A2

Features you need, Prices you want.

Mono-Lock

The Mono-Lock feature allows for quick and easy adjustments to the height of the tripod. The user can easily change leg stages without the hassle of multiple locks.

Monitor Mounting Points

Attaching your monitor has never been easier; with mounting points directly on the head of the tripod you can easily see your monitor no matter how you may need to move the camera while shooting.

What's Included

- 1 x GH10 Head
- 1 x GA752 Aluminum Tripod Legs
- 1 x GB2 Pan Handle
- 1 x GS01 Mid-Level Spreader
- 1 x T20 Tripod Bag
- 1 x F3 Rubber Feet

Optional Accessories

- EI-7004** Tripod Dolly
- 100BF** 100mm Ball to Flat Adapter
- EI7500** Hi-Hat w/ 75/100mm Bowl
- IK-RSR6** 6" Hi-Hat Riser
- IK-RSRS** 6" Camera Riser Hi-Hat w/ Swivel
- GB3** Handle for GH15/25 Heavy Duty Heads
- MA211-R** 11" Articulating Arm w/ Single Rod Mount
- MA207** 7" Articulating Arm
- MA211** 11" Articulating Arm

Specifications

Bowl Size	75mm
Build Material	Aluminum
Camera Plate Size	120 x 45 x 11mm
Camera Plate System	Sliding Base Plate w/ Safety Locks
Counterbalance Settings	1-7
Pan Drag Settings	0-5
Tilt Drag Settings	0-5
Head Mount/Base	75mm Ball
Head Weight	4 lbs
Height Range	32.25" - 72.5"
Leg Payload Capacity	22 lbs
Leg Weight	12 lbs
Material	Aluminum
Max Height Spreader Closed	72.5"
Max Height Spreader Open	67.5"
Min Height Spreader Open	32.25"
Min Height Spreader Closed	34.5"
Pan Handle Style	Telescoping Length
Pan Lock	Thumb Lock
Pan Range	360°
Shipping Dimensions	40.5" x 9.5" x 9.5"
Shipping Weight	20 lbs
Temperature Range	-40°C ~ +80°C
Tilt Lock	Thumb Lock
Tilt Range	-60°C ~ +90°C
Transport Length	36"

