

EG15A2

2 Stage Aluminum Tripod w/ GH15 Head (E-Image)

ONE SHEET

Overview

The EG15A2's features includes the E-Image Mono-Lock design, and a 10 step counterbalance that delivers reliable performance that rises above competitors in its price range and class.

The Kit supports cameras and accessories weighing up to 33 pounds. The GA102 tripod is made of lightweight aluminum, has a 100mm bowl, and the legs are a twin tube design with two stages. The Mono-Lock feature allows for quick height adjustments of both stages with one twist. The EG15A2 extends to a maximum height of 69.5" and a minimum height of 24.5". Included are both floor spreader and adjustable mid-level spreader with feet providing extra security and stability on different terrains.



EG15A2 | 2 Stage Aluminum Tripod w/ GH15 Head (E-Image) | UPC Code: 847983009787

Special Features

- Supports 33lbs 15kg | 100mm ball
- 2 Stage Leg Design with Mono-Lock
- Height Range 24.5" to 69.5"
- 0-5 Drag Adjustment Settings
- 0-9 Counter Balance Settings
- ¼" - 20 Threaded Accessory Socket for Monitor Arm
- Separate Pan/Tilt Locks
- Both Mid-Level Spreader with Feet and Ground Spreader Included
- Illuminated Spirit Level
- Heavy Duty Padded Bag with Back-Pack Straps & Shoulder Strap

Recommended For

- Studio or Location Use
- Professional Cinematography
- Professional Photography
- Support Sliders, Jibs, and Gear



www.facebook.com/ikanseeit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

ikan

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com

EG15A2

Features you need, Prices you want.

Mono-Lock

The Mono-Lock feature allows for quick and easy adjustments to the height of the tripod. The user can easily change leg stages without the hassle of multiple locks.

Multiple Spreaders

Comes with both a Mid & Ground-Level Spreaders.

Monitor Mounting Points

Attaching your monitor has never been easier; with mounting points directly on the head of the tripod you can easily see your monitor no matter how you may need to move the camera while shooting.

Bubble Level

The head incorporates an illuminated bubble level you assist as the user sets up for any kind of shoot.

What's Included

- 1 x GH15 Fluid Head
- 1 x GA102 Tripod Legs
- 1 x F3 Tripod Rubber Feet
- 1 x GB2 Telescoping Handle
- 1 x GS01 Mid-Level Spreader
- 1 x GS02 Ground Spreader
- 1 x T30 Tripod Bag

Optional Accessories

- EI-7004** Tripod Dolly
- 100BF** 100mm Ball to Flat Adapter
- EI7500** Hi-Hat w/ 75/100mm Bowl
- IK-RSR6** 6" Hi-Hat Riser
- IK-RSRS** 6" Camera Riser Hi-Hat w/ Swivel
- GB3** Handle for GH15/25 Heavy Duty Heads
- MA211-R** 11" Articulating Arm w/ Single Rod Mount
- MA207** 7" Articulating Arm
- MA211** 11" Articulating Arm

Specifications

| | |
|----------------------------|------------------------------------|
| Bowl Size | 100mm |
| Bubble Level | Illuminated |
| Build Material | Carbon Fiber |
| Camera Plate Size | 120 x 45 x 11mm |
| Camera Plate System | Sliding Base Plate w/ Safety Locks |
| Tilt Drag Settings | 0-5 |
| Counterbalance Settings | 0-9 |
| Pan Drag Settings | 0-5 |
| Counterbalance System | Stepped |
| Head Mount/Base | 100mm Ball |
| Head Weight | 8 lbs |
| Height Range | 24.5" - 69.5" |
| Leg Payload Capacity | 33 lbs |
| Leg Weight | 14.7 lbs |
| Max Height Spreader Closed | 69.5" |
| Max Height Spreader Open | 65" |
| Min Height Spreader Open | 24.5" |
| Min Height Spreader Closed | 32" |
| Pan Handle Style | Telescoping length 570mm |
| Pan Lock | Thumb Lock |
| Pan Range | 360° |
| Shipping Dimensions | 39" x 10" x 9.5" |
| Shipping Weight | 27 lbs |
| Spreader Type | Floor & Mid-Level Spreader w/ Feet |
| Temperature Range | -40° C ~ +80° C |
| Tilt Lock | Thumb Lock |
| Tilt Range | -75° C ~ +90° C |
| Transport Length | 36" |

