

EG15C2

2 Stage Carbon Fiber Tripod w/ GH15 Head (E-Image)

ONE SHEET

Overview

The E-image EG15C2 Carbon Fiber Tripod Kit is engineered for the pro shooter in mind. From small cameras to fully accessorized rigs its capacity ranges up to 33 lbs. Its two stage tripod legs are effortless to set up, adjust, and collapse.

The Mono-Lock feature allows leg adjustments with a single twist for both stages moving quickly from height ranges 18" up to 63". Included in the kit the GH15 Head uses a stepped fluid Pan and Tilt drag system with 5 settings that support up to 33lb cameras. The 0-9 stepped counterbalance settings provide confident counterforce for different weighted cameras. Get smooth moves with the EG15C2 Tripod Kit.



EG15C2 | 2 Stage Carbon Fiber Tripod w/ GH15 Head (E-Image) | UPC Code: 847983010677

Special Features

- Supports 33lbs (15kg) Carbon Fiber
- 2 Stage Leg Design with Mono-Lock
- 0-5 Drag Adjustment Settings - 0-9 Counter Balance Settings
- Both Mid-Level Spreader with Feet and Ground Spreader Included
- 100mm ball/bowl
- 1/4"- 20 Threaded Accessory Socket for Monitor Arm
- Separate Pan/Tilt Locks
- Lightweight Carbon Fiber Legs
- Illuminated Spirit Level
- Heavy Duty Padded Bag with Back-Pack Straps & Shoulder Strap

Recommended For

- Studio or Location Use
- Professional Cinematography
- Professional Photography
- Support Sliders, Jibs, and Gear



www.facebook.com/ikanseeit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

ikan

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com

EG1502

Features you need, Prices you want.

Adjustable Drag Controls

Finding the right balance for your rig is easy with the 9 levels of counterbalance of 6 levels of drag control.

Unique Mono-Lock Legs

The GC102 legs employ the Mono-Lock system for simple height adjustment from 18-63" for all 3 leg stages with just one twist of the knob.

Accessory Mounts

A 1/4"-20 and 3/8"-16 thread mounting point allows accessories like monitors to be mounted off of the camera while they still pan and tilt with your camera.

Illuminated Bubble Level

Quickly level the 100mm head with its momentary illuminated bubble level.

Multiple Level Spreaders

Included are both floor spreader & adjustable mid-level spreader with feet providing extra security and stability on different terrains.

Lightweight Carbon Fiber

10 Layer lightweight carbon fiber benefits include: Lighter to carry, cool to the touch, quieter set-up, & less vibration than aluminum.

What's Included

- 1 x GH15 GH15 Fluid Head
- 1 x GC102 Carbon Fiber Leg
- 1 x GS02 Mid Level Spreader
- 1 x GS01 Ground Level Spreader
- 1 x F3 Feet
- 1 x T20 Soft Sided Tripod Bag
- 1 x GB3 Pan Handle

Optional Accessories

- EI-7004** Tripod Dolly
- 100BF** 100mm Ball to Flat Adapter
- EI7500** Hi-Hat w/ 75/100mm Bowl
- IK-RSR6** 6" Hi-Hat Riser
- IK-RSRS** 6" Camera Riser Hi-Hat w/ Swivel
- GB3** Handle for GH15/25 Heavy Duty Heads
- MA211-R** 11" Articulating Arm w/ Single Rod Mount
- MA207** 7" Articulating Arm
- MA211** 11" Articulating Arm

Specifications

Bowl Size	100mm
Bubble Level	Illuminated
Build Material	Carbon Fiber
Camera Plate Size	120 x 45 x 11mm
Camera Plate System	Sliding Base Plate w/ Safety Locks
Tilt Drag Settings	0-5
Counterbalance Settings	0-9
Pan Drag Settings	0-5
Counterbalance System	Stepped
Head Load Settings	33 lbs
Head Mount/Base	100mm Ball
Head Weight	8 lbs
Height Range	24.5"-69.5"
Leg Payload Capacity	133 lbs
Leg Weight	14.7 lbs
Max Height Spreader Closed	69.5"
Max Height Spreader Open	65"
Min Height Spreader Open	24.5"
Min Height Spreader Closed	32"
Pan Handle Style	Telescoping length 570mm
Pan Lock	Thumb Lock
Pan Range	360°
Shipping Dimensions	39 x 10 x 9.5 In.
Shipping Weight	24 lbs
Spreader Type	Floor & Mid-Level Spreader w/ Feet
Temperature Range	-40° C ~ +80° C
Tilt Lock	Thumb Lock
Tilt Range	-75° C ~ +90° C
Transport Length	36"

