

# **Overview**

The E-Image Pedestal Kit comes complete out of the box as an affordable camera pedestal and includes the E-Image Pedestal Dolly, Tripod, and Tripod Bag.



## EI-GH25-KIT | Pedestal Kit Includes AT7902 Base/Dolly & GH25 Head | UPC Code: 847983009473

# **Special Features**

- Payload Range 25Kg | 55lbs | Bowl Size: 100mm ball level feature
- 0-7 Grades of drag for Tilt and Pan I Pan and Tilt Locks
- Counter Balance Adjustment 1-15
- Parking Hole for Monitor Arm
- Sliding Base plate with safety lock and retractable registration pin
- Illuminated Spirit Level
- Dual Sided Pan/Tilt Arm Rosette Mounts (two arms included)
- Heavy Duty Telescoping Pan/Tilt Arms

kan

• Two Stage Aluminum Tripod Legs with Mid-Spreader Positive Leg Locking

# **Recommended For**

- Professional Cinematography
- Professional Photography
- Studio or Location Shooting





- www.vimeo.com/ikancorp
- www.youtube.com/ikancorp

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com

# EI-GH25-KIT

#### Mono-Lock

The Mono-Lock feature allows for quick and easy adjustments to the height of the tripod. The user can easily change leg stages without the hassle of multiple locks.

## GH25 Head

The E-Image GH25 Head employs a stepped fluid Pan and Tilt drag system setting that supports up to 55 lbs of payload. The 1-15 steps of counterbalance settings provide confident counterforce for different weighted cameras.

## **Monitor Mounting Points**

Attaching your monitor has never been easier; with mounting points directly on the head of the tripod you can easily see your monitor no matter how you may need to move the camera while shooting.

## Pedestal Kit Tripod

The E-Image GH25 dolly's two stage aluminum tripod legs have a mid-spreader positive leg locking system and a dolly spreader with lockable wheels.

## What's Included

1 x EI-7005 E-Image Pedestal Dolly 1 x EI-AT7902A E-Image Pedestal Tripod 1 x EI-GH25 Fluid Head With GB3 Pan Bars (2) 1 x GP2 Camera Plate

1 x T30 Tripod Bag

## **Optional Accessories**

EI-7004	Tripod Dolly
EI7500	Hi-Hat w/ 75/100mm Bowl
IK-RSR6	6" Hi-Hat Riser
IK-RSRS	6" Camera Riser Hi-Hat w/ Swivel
GB3	Handle for GH15/25 Heavy Duty Heads
MA211-R	11" Articulating Arm w/ Single Rod Mount
MA207	7" Articulating Arm
MA211	11" Articulating Arm

# Features you need, Prices you want.

Specifications	
Bowl Size	100mm Riser Bowl
Bubble Level	Illuminated Bubble Level
<b>Build Material</b>	Aluminum
Camera Plate Size	160 x 70 x 13mm
Camera Plate System	Sliding Base Plate w/ Safety Locks
Counterbalance Settings	1-15
Counterbalance System	Stepped
Pan Drag Settings	0-7
Tilt Drag Settings	0-7
Head Load Capacity	55 lbs
Head Mount/Base	100mm Ball
Head Weight	9 lbs
Height Range	Working Height Range 47" -87"
Leg Payload Capacity	55 lbs
Pan Handle Style	Twin Telescoping Grip length 575mm
Pan Lock	Thumb Lock
Pan Range	360°
Shipping Dimensions	48" x 12" x 12"
Shipping Weight	40 lbs
Temperature Range	-40°C ~ +80°C
Tilt Lock	Thumb Lock
Tilt Range	-80°C ~ +90°C
Transport Length	46"

