

**ONE SHEET** 

## **Overview**

The E-Image ES50 slider uses a unique tracking mechanism that provides 29" of sliding range in a unit that is only 20" long. Its 16 layer carbon fiber frame and CNC machined components form the core of a ruggedly sturdy slider that is both durable yet smooth in operation. This slider is perfect for run-and-gun style shooters who require maximum quality video with minimal gear. The shuttle of the ES50 will accept both 1/4"-20 and 3/8"-16 threading and will operate smoothly with payloads up to 17.6 lbs.



ES50 | 29" Double Slider (E-Image) | UPC Code: 847983019588

## **Special Features**

- 29" of travel in a 20" length slider
- Can be used on any flat surface or mounted to a tripod
- Perfect for shooters who require maximum use with minimal size & weight
- Camera mounting plate compatible with cameras requiring either 1/4"-20 or 3/8"-16 mounting
- Includes variable tension knob for adjusting the slider to travel
- Includes durable travel case

ikan

### **Recommended For**

- Wedding Video
- Cinematography
- Nature Video



www.ikancorp.com 1.713.272.8822 sales@i

sales@ikancorp.com

# **ES50**

## Features you need, Prices you want.

#### Bearing

Its sophisticated bearing provides smooth and quiet movement.

#### Feet

The ES50 has adjustable feet for use on the ground.

#### **Multiple Mounting Options**

With 1/4"-20 and 3/8"-16 thread holes in the bottom, the slider can be placed on any tripod.

#### **Durable Case**

A durable travel case provides a safe home for the ES50 while on-the-go.

#### What's Included

1 x ES50 29" Double Slider

1 x Carry Case

Dual-Sided Follow Focus Core Specifications		
Dimensions	19.7 x 5.3 x 3.5 in.	
Sliding Range on Tripod	29.1 in.	
Sliding Range on Ground	14.6 in.	
Net Weight	4.2 lbs	
Maximum Payload	17.6 lbs	

Shipping Specifications	
Shipping Dimensions	21 x 6.75 x 4 in.
Shipping Weight	6 lbs

#### **Optional Accessories**

GH03F	Flat Base Pro Fluid Video Head 11lbs Max (E-Image)
IK-RSR3	3" Camera Riser
IK-RSR6	6" Hi-Hat Riser

