# EVF35-KIT

3.5" 4K Support HDMI Electronic Viewfinder LCD

Monitor Kit

ONE SHEET

#### Overview

Big things come in small packages. That is definitely the case with the VL35. This monitor packs a lot of features in its compact size. The biggest feature is its 4K capabilities. This 3'.5display is able to take your 4K and Ultra HD footage and to help you focus it also features a Pixel-to-Pixel mode so despite its small size you can still focus reliably. Its small size makes it ideal for lightweight camera systems and gimbals. Especially cameras without a built-in display. Now we have increased the versatility of this tiny workhorse and created an EVF kit. This kit turns the VL35 into a 4K electronic viewfinder giving you a clearer picture.



EVF35-KIT | 3.5" 4K Support HDMI Electronic Viewfinder LCD Monitor Kit | UPC Code: 847983019984

### **Special Features**

- Resolution of 800x480
- 4K & Ultra HD Support via HDMI
- HDMI Input & Output
- · Composite Input
- Histogram
- · Peaking, False Color, Pixel-to-Pixel & Clip Guides
- · Headphone Output



#### Recommended For

- Independent Film Makers
- DSLR Video Shooters
- · Mirrorless Camera Video Shooters



www.facebook.com/ikanseeit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com

## EVF35-KIT

#### Increased Sharpness & Clearer Picture

The EVF35 Viewfinder allows you to get the most out of the VL35 Monitor. It features high quality glass with diopter adjustment to get the image as sharp as possible. The viewfinder attaches via magnets that allow a strong hold but can be removed if needed.

#### Big 4K Capabilities in a Small Size

The VL35 can take a 4K or Ultra HD image and scale it down to its native resolution producing a superbly sharp image. Ikan realizes that attempting to focus such a high resolution image on such a small screen could caus focus issues so we included a 1:1 Pixel-to-Pixel mode so you can get right down to the individual pixels to make sure you are in focus. This feature is also useful for HD footage as well.

#### Small & Lightweight

The VL35's diminutive size comes in handy in tight spaces and where weight savings are important, such as with gimbals. Also with today's ever-shrinking cameras sometimes the built-in screen is no longer included, necessitating an external monitor.

#### Inputs & Outputs

The VL35 includes HDMI Input & output as well as composite input via a 3.5mm connector. For audio monitoring, it also features a headphone output. For future firmware updates there is also a full size USE connector.

#### Software Features

To assist you during your productions, the VL35 features all of our standard software features such as false color & histogram to get the right exposure, peaking for auto assist, pixel-to-pixel, frame guides and many more.

#### In the Box

The VL35-KIT comes included with: VL35 Monitor, EVF35 Viewfinder, Carry Pouch, Canon E6 Battery Plate, Screen Cleaning Wipes, USB Drive, AV Cables, and AC Adapter.

#### What's Included

- 1 x 12V AC Adapter
- 1 x AV Break Out Cable
- 1 x Canon E6 Battery Plate
- 1 x Carry Pouch
- 1 x EVF35 Viewfinder
- 1 x Screen Cleaning Wipe
- 1 x VL35 Monitor

#### Features you need, Prices you want.

Monitor Specs	
Backlight	LED
Color Depth	16.7 Million
Color System	PAL / NTSC / SECAM (Auto-Detected
Contrast Ratio	800:1
Diagonal (Inch)	3.5 in.
Dimensions	4 x 2.9 x 0.7 in. (Monitor)
Inputs	104 x 74.2 x 20.1 mm (Monitor)
LCD Brightness	HDMI, Composite
Material	315 cd/m2
Operating Volts	Heavy Duty Plastic
Outputs	DC 6 to 24V
Power Consumption	2.5W
Resolution	800x480
Surface Treatment	Anti-Glare
Viewing Angle	160 (H) 160 (V)
Weight	0.52 lbs

Shipping Specs	
Shipping Dimensions	7.2 x 8 x 4.2 in.
Shipping Weight	2 lbs

Video Signal Support Specs		
HDMI	720x480i & 720x480p @ 59.94, 60 Hz	
	720x576i @ 50 Hz	
	1280x720p @ 23.97, 24, 29.97, 30, 50, 59.94, 60 Hz	
	1920x1080i @ 50, 59.94, 60 Hz	
	1920x1080psf @ 24, 25, 29.97, 30 Hz	
	1920x1080p @ 23.97, 24, 25, 29.97, 30, 50, 59.94, 60 Hz	
	3840x2160p @ 24, 25, 30 Hz	
	4096x2160p @ 24 Hz	
Composite	NTSC-M, NTSC-J, NTSC 4.43	
	PAL B/G H I D, PAL M, PAL N	
	SECAM	

#### Optional Accessories

MA207 7" Articulating Arm MA211 11" Articulating Arm

IBC-E6+ Canon LP-E6 Compatible Battery ICH-E6 Canon LP-E6 Compatible Charger





