

FLY-X3-GO

3-Axis GoPro Gimbal Stabilizer

ONE SHEET

Overview

The Fly-X3-GO 3 Axis Gimbal Stabilizer offers creative mounting and smooth operation of your GoPro. It provides better control and stability for those unique shots that set it apart from other competitors. The FLY-X3-GO can also be mounted on a monopod, boompole or roll bar mount. It comes with an included extension cable, which controls the yaw, pitch and roll.



FLY-X3-GO | 3-Axis GoPro Gimbal Stabilizer | **UPC Code:** 847983015443

Special Features

- Quick Setup
- Easy-to-Use
- Ready-to-use Out of the Box
- 5 Way Joystick offers Complete Control over Pan/Tilt & Modes
- Mounts to Existing GoPro Mounts
- Includes 1.5m Control Cable

Recommended For

- Portable Cinematography
- GoPro Enthusiasts



www.facebook.com/ikanseit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

ikan

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com

FLY-X3-GO

Features you need, Prices you want.

Quick Setup

The FLY-X3-GO comes pre-programmed and ready-to-use out of the box. Simply charge and GO!

Options

Among the options include a 5-way joystick that offers complete control over pan/tilt and an extensive mode selection.

Mount-ability

The FLY-X3-GO is equipped with the standard GoPro mount. If you remove the GoPro mount, there is also a 1/4"-20 Mounting point for extra versatility.

Included Control Cable

A 1.5-meter control cable can control the yaw, pitch and roll while the gimbal is mounted on a monopod, boom pole, etc.

Power

The FLY-X3-GO can also power your GoPro camera!

What's Included

- 1 x 3-Axis Handheld Gimbal Platform
- 1 x Gimbal Handle
- 2 x 18350 Li-Ion Battery
- 1 x Battery Extender
- 1 x Detachable Control Cable 1.5m
- 1 x Micro USB Camera Charging Cable
- 1 x Micro USB Battery Charging Cable
- 1 x Battery Charger

Specs

Material	Aluminum
Pitch Angle	260°
Roll Angle	80°
Yaw Angle	300°
Operating Voltage	6.5V - 12.6V
Operating Current	Standard 120Ma
Battery	900mAh 18350 Li-Ion Battery
Operating Time	4 Hours
Operating Temperature	-10°~40°
Dimensions	274 x 117 x 93 mm
Weight	1.25 lbs
Shipping Dimensions	8.5 x 7 x 7 In.
Shipping Weight	3 lbs

Optional Accessories

FX3G-SES	Fly-X3-GO Session Frame Mount
iLED-MA	Micro Flood Light
iLED-MS	Micro Spot On-Camera Light
MA207	7" Articulating Arm
MA211	11" Articulating Arm
MA211-R	11" Articulating Arm w/Single Rod Mount

