

# ON-Camera Type FM-073SC



- Zero/Under/Over Scan
- Supporting 3G-SDI (Level A/B)
- False Color
- Exposure Range Check
- Supporting parade mode
- Monitor Control/Update via RS-422
- 10-bit Signal Processor
- Remote Control via GPI(RJ-45) Port
- Firmware Update via USB Memory
- Tally automatically turns on When recording(Arri, Red)

## FM-073SC

FM-073SC is an on-camera monitor with the advanced features including auto flip, H/V level meters, various zoom modes for DSLR, and embedded 1:1 SDI-HDMI, HDMI-SDI converters.

LCD			
Size	7"	Luminance of White	400 cd/m <sup>2</sup>
Resolution	1024 x 600	Contrast	900 : 1
Color	8bit	Pixel Pitch	0.15 x 0.15mm
Viewing Angle	160(H), 160(V)	Display Area (H x V)	153.6 x 90.0 mm
Back Light	LED		
Input			
3G/HD/SD-SDI	HDMI, (with HDCP v.1.1), 19pin Female		
Analog(YPbPr/CVBS/S-Video/RGB)			
Output			
Selectable SDI-1/2 Loop-through or HDMI conversion Out	HDMI, 19-pin Female		
Input Signal Format			
SMPTE 425M AB	SMPTE 274M/292M	SMPTE 296M	SMPTE 260M
SMPTE 125M/259M	2K, SMPTE 428M	ITU R-BT.656	HDMI
Audio In/Out			
1 x Headphone Jack Out	1 x Headphone Jack In	1 x Speaker Out	
Weight			
0.87kg / 1.92lbs			

\* Optional accessories available

- Waveform/Vectorscope
- Various Markers
- 3 Color TALLY Lamp
- UMD Mode Display
- H/V Delay, RGB/Mono
- Focus Assistance
- Pixel-to-Pixel View
- Time Code Display(SDI Only)
- PiP, PaP (Between SDI & HDMI Input)
- V-CHIP display (SDI Only)
- Tally automatically turns on When recording(Arri, Red)
- Copying the preset data to another monitor by USB memory
- R/G/B and White Internal Patterns Display