

# Field Type Super Bright

# FM-073SCH Best Rated



- Supporting 3G-SDI (Level A/B)
- Firmware Update via USB Memory
- Waveform / Vector scope
- DV- Battery Level Indicator
- Horizontal/Vertical Level Meters
- Time Code(Except 3G Level B)
- Auto Color Temperature Adjustment
- Compatible to various DSLR Output
- HDMI-to-SDI & SDI-to-HDMI Converter
- Various Markers (EBU, 4:3, 16:9, 1.85:1, 2.35:1, etc.)
- 8~16ch Audio Level Meter
- False Color
- Auto Flip
- H/V Flip

## FM-073SCH

FM-073SCH is a super bright on-camera monitor with the luminance of n 1100 cd/m<sup>2</sup>, which allows users monitor the images at any angle in sunlight. It comes with auto flip, PiP, H/V level meters, various zoom modes for DSLR, still image overlay, embedded 1:1, SDI-HDMI, HDMI-SDI conversions and SDI Loop-Through or HDMI conversion.

LCD			
Size	7.0"		
Resolution	1024 x 600		
Pixel Pitch	0.15 x 0.15 mm		
Color	8bit		
Viewing Angle	160(H), 160(V)		
Luminance of White	1100 cd/m <sup>2</sup>		
Contrast	900 : 1		
Back Light	LED		
Display Area (H x V)	153.6 x 90.0 mm		
Input			
3G/HD/SD-SDI	HDMI(with HDCP v.1.1) 19pin Female		
Analog(YPbPr/CVBS/S-Video/RGB)			
Output			
Selectable SDI-1/2 Loop-through or HDMI conversion Out	HDMI 19-pin Female		
Analog Input			
Composite	YC(S-Video)	Component(Y/Pb/Pr)	Component (R/G/B)
Input Signal Format			
SMPTE 425M AB	SMPTE 274M/292M	SMPTE 296M	SMPTE 260M
SMPTE 125M/259M	2K, SMPTE 428M	ITU R-BT.656	HDMI
Audio In / Out			
1 x Headphone Jack In	1 x Headphone Jack Out	1 x Speaker Out	
Weight			
<b>1.3kg / 2.86lbs</b>			

\* Optional accessories available

- Tally automatically turns on When recording(Arri, Red)
- H/V Delay, Pixel-to-Pixel View, Zero/Under/Over Scan, Blue/Mono