

HF40-KIT

Helia 40 Watt Bi-Color LED 3-PT Light Kit

ONE SHEET

Overview

The Helia Bi-Color LED lights offer the flexibility of color temperatures ranging from 2700K to 5600K for any shooting situation. The 4-inch Fresnel lenses can focus from a 60-degree flood to a 15-degree spot. With a high CRI and TLCI, the Helias give shooters all the color they're looking for and more.

A large digital display allows you to move through the menus and tweak settings with ease. The flicker feature can be tuned to any frequency. HF40 lights can be powered with a pro battery and come with V-mount battery plates and DC cables. They also come with barn doors and AC power cables. A heavy-duty case and sturdy stands allow for quick setups wherever you choose to shoot.



HF40-KIT | Helia 40 Watt Bi-Color LED 3-PT Light Kit | **UPC Code:** 847983014460

Special Features

- Bi-Color Light adjustable from 2700K-5600K
- 4" Fresnel with flood to spot
- High CRI and TLCI
- Can be powered by Pro V-Mount Battery
- Flicker feature allows slow to fast strobe
- Large digital readout for easy adjustment
- Long LED Lifespan
- Barn Doors Included
- Includes Hard Case with Wheels

Recommended For

- Studio Lighting
- Interviews

ikan

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com



www.facebook.com/ikanseeit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

HF40-KIT

Features you need, Prices you want.

Adjustable Bi-Color Light

Bi-Color light can be adjusted simply by turning the knob and dialing in the correct color temperature.

Spot to Flood Fresnel

Spot-to-flood adjustment.

Battery Options

Pro Battery options available.

Large Digital Readout

The large LCD Screen allows you to see all menu settings when making changes.

Flicker Feature

The flicker setting allows for special effect lighting or for dialing in the flicker frequency for camera speed.

Heavy Duty Custom Case

The heavy-duty case and stand allow for quick setups in virtually any situation.

What's Included

- 1 x Hard Case
- 3 x 40 Watt Light Fixture
- 3 x 6Ft Power Cable
- 3 x Barn Doors
- 3 x Light Stands
- 3 x P-TAP Cables
- 3 x V-Mount Plates
- 3 x Yoke

Accessories

- KCP-703 Stage Clamp w/ 16mm Stud
- SW-04 Safety Wire
- MK350 Spectrometer from UPRtek

Specifications

Beam Angle	18-60°
Build Material	Aluminum
Control	Toggle Button with Knob
Cooling System	Active Cooling Fan
Dimming	Flicker-Free On-Board 100-0%
Fixture Size	8.5 x 7.5 x 13 in.
Fixture Weight	5 lbs
Focusing	Rotating Rear Knob
Head Type	2700-5600K
Lens	4" Glass Fresnel
Light Source	1x40 Watt LED Bi-Color
Power Supply	6 ft Power Cable
Rating	AC Volts 120 AC, 50-60 Hz, 40 Watts
Yoke	Cast Aluminum with 1 1/8" Pin

Photometrics - LUX

Spot 2700K	1.5m - 2060 LUX	3m - 610 LUX	4.5m - 152 LUX
Flood 2700K	1.5m - 1043 LUX	3m - 307 LUX	4.5m - 288 LUX
Spot 3200K	1.5m - 2015 LUX	3m - 677 LUX	4.5m - 325 LUX
Flood 3200K	1.5m - 1086 LUX	3m - 332 LUX	4.5m - 161 LUX
Spot 5600K	1.5m - 2361 LUX	3m - 762 LUX	4.5m - 361 LUX
Flood 5600K	1.5m - 1281 LUX	3m - 373 LUX	4.5m - 180 LUX

Photometrics - Footcandles

Spot 2700K	5ft - 191 FC	10ft - 57 FC	15ft - 14 FC
Flood 2700K	5ft - 97 FC	10ft - 29 FC	15ft - 27 FC
Spot 3200K	5ft - 187 FC	10ft - 63 FC	15ft - 30 FC
Flood 3200K	5ft - 101 FC	10ft - 31 FC	15ft - 15 FC
Spot 5600K	5ft - 219 FC	10ft - 71 FC	15ft - 34 FC
Flood 5600K	5ft - 119 FC	10ft - 35 FC	15ft - 17 FC

Shipping Specifications

Shipping Dimensions	33 x 22 x 13 in.
Shipping Weight	25 lbs

