

IDK4312-v2

Kit with 4 x iLED312-v2

ONE SHEET

Overview

The IDK4312-v2 Kit with 4 x iLED312-v2 is designed and built for imaging professionals who want high quality at an affordable price.

The 4-Point Light Kit features include bi-color capability and a wide 60-degree angle that delivers reliable, consistent performance.

The iLED312-v2 Bi-Color LED Light features energy efficient LED lights that allow you to easily adjust and control the color temperature on the digital readout between 3200K Tungsten and 5600K Daylight using the rotary knobs. The compact design with integrated horizontal and vertical interlock makes the iLED312-v2 portable and easy to set up. A removable diffusion gel filter is included and the slide-on barn doors can be folded flat for transportation.



IDK4312-v2 | Kit with 4 x iLED312-v2 | UPC Code: 847983007868

Special Features

- Color Temperature of 5600K/3200K (300K)
- Includes (4) iLED312-v2 Lights with Stands and Bags
- Includes AC Adapters, Batteries and Chargers
- Energy Efficient and Lightweight

Recommended For

- Studio Lighting
- Portrait Photography
- Interviews

ikan

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com



www.facebook.com/ikanseeit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

IDK4312-v2

Features you need, Prices you want.

Wide Angle Beam Pattern

The 7 ¾" x 4 ½" light contains 312 energy-efficient LEDs and delivers field-tested reliability, solid construction, and other features essential to professional performance such as bi-color capability and a wide, 60-degree angle.

Digital Readout Display

An easy-to-view digital readout indicates battery life as you shoot, as well as; brightness level and color temperature, for the simplest of adjustments.



Horizontal/Vertical Interlock Options

The iLED312-v2 has the capability to interlock with multiple units to create a larger, more intense light.

What's Included

- 4 x iLED312-v2 Lights
- AC Adapters
- Batteries & Charger
- 4 x Light Stand
- Light Bag

Specifications

Beam Angle	60°
Brightness	3' / 722 lux / 3200K
Build Material	Heavy Duty Plastic
Color Temperature	3200K - 5600K
Control	Local Knob Controls
Cooling System	Passive Cooling
Dimensions	19" x 11.5" x 3.5"
Dimming	10-100%
Fixture Size	7.75" x 1.5" x 4.5"
Fixture Weight	1.5 lbs
Focusing	NO
Head Type	Bi-Color
Lens	60° Lens
Light Source	156 0.06w LEDs 5600K / 156 0.06w LEDs 3200K
Mount	Stand Mount
Power Supply	12v @ 2 Amps
Rating	120v @ 60Hz
Voltage	7.4v-14.8v
Shipping Weight	22 lbs

Optional Accessories

- LCGK-2** Large Creative Gel Kit
- IBS-1170** Sony "L" Series Compatible High Capacity Battery
- IBS-970** Sony "L" Series NP-F970 Compatible Battery
- CP-STND** Compact Light Stand

Photometrics

