

IFB1024

Featherweight Bi-Color LED Light with AB & V-Mount Plates

ONE SHEET

Overview

The IFB1024 Featherweight Bi-Color LED Light features 1024 LED lights that allow you to easily adjust and control the color temperature between 3200K Tungsten and 5600K Daylight using the LCD touchscreen.

Large rotary knobs and an included remote are also offered for dimming and dialing in color temperature. The integrated yoke mount makes the IFB1024 easy to set up. A multi-voltage DC power supply is included and for portable power a pro battery plate for both Sony V-mount and Anton Bauer is supplied.

A removable diffuser is included and the pre-mounted four leaf barn doors with intensifiers can be folded flat for transportation.



IFB1024 | Featherweight Bi-Color LED Light with AB & V-Mount Plates | **UPC Code:** 847983008919

Special Features

- Ultra-light, Compact, Dual-Color Light
- LCD Touch-Screen Controller with Dimmer Knobs
- Includes Pro Battery Plates for Anton Bauer & Sony V-mount;
- Yoke Mount, Barn Doors with Removable Intensifiers, and Diffuser

Recommended For

- Studio Lighting
- Product Photography

ikan

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com



www.facebook.com/ikanseit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

IFB1024

Features you need, Prices you want.

Full-Spectrum, Cinema Quality Color

With Bi-Color LED bulbs, ikan's IFD576 is a powerful flood light that lets you enjoy soft, beautiful light and excellent color purity in just about any shooting scenario. This is the LED light you've been looking for.

Easy-to-Adjust Light Intensity

With a touch-sensitive digital display, a dimmer knob, and a remote control, you have options when it comes to adjusting the light intensity. The IFB1024 puts you in control so you can get the perfect lighting for your shot every time.

Exceptional Quality

As the IFB1024 light comes equipped with an AB to V-Mount pro battery plate, barn doors with intensifiers, diffuser, power supply, remote control, and yoke mount, it is an exceptional value.

What's Included

- 1 x IFB1024 Light
- 1 x AB Mount (Attached)
- 1 x AB to V-Mount Adapter
- 1 x Diffuser
- 1 x Power Supply
- 1 x Remote Control
- 1 x Yoke

IFB1024 Lights Available in Multiple Kits

IFB1024-2PT-KIT
IFB2511

IFB1024-KIT
IFB2115


Specifications

Beam Angle	50°
Build Material	Heavy Duty Plastic
Color Temperature	3200K(±200K) / 4000K(±200K) / 5600K (±200K)
Control	Local Knob & Touchscreen
Cooling System	Passive Heat Sync
Dimming	10-100%
Fixture Size	14" x 14" x 3.75"
Fixture Weight	6 lbs
Focusing	N/A
Head Type	Bi-Color
Lens	60° Lens
Light Source	512 0.06w LED @5600K 512 0.06w LED @ 3200K
Mount	Yoke
Operating Wattage	82 w @ 120v/60Hz
Power Supply	12v @ 6.66 Amp
Rating	120v @ 60 Hz
Shipping Weight	11.2 lbs
Shipping Dimensions	17.75" x 19.5" x 5"

Optional Accessories

- C-2KA-KIT** AB Mount Pro Power System
- C-2KS-KIT** V-Mount Portable Pro Power System
- PWRGP-1** Power Grip
- ID500-PS** Power Supply for ID500/IB500
- ID500-RC** Remote Control for ikan Lights
- CH1546** Chimera for IFB546/IFD576

Photometrics



ikan

Houston, Texas

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com