

ONE SHEE

Overview

The IFD1024 Featherweight Daylight LED Light features 1024 energy efficient LED lights that are dimmable using the LCD touchscreen.

A large rotary knob and an included remote are also used for dimming. The compact design with integrated yoke mount makes the IFD1024 portable and easy to set up. A multi-voltage DC power supply is included and for portable power a pro battery plate for both Sony V-mount and Anton Bauer is supplied.

A removable diffuser is included and the premounted four leaf barn doors with intensifiers can be folded flat for transportation.



IFD1024 | Featherweight Daylight LED Light with AB & V-Mount Plates | UPC Code: 847983008933

Special Features

Ultra-light, Compact, Dual-Color Light

ikan

- LCD Touch-Screen Controller with Dimmer Knobs
- Includes Pro Battery Plates for Anton Bauer & Sony V-mount;
- Yoke Mount, Barn Doors with Removable Intensifiers, and Diffuser

Recommended For

- Studio Lighting
- Product Photography





www.vimeo.com/ikancorp



www.youtube.com/ikancorp

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com

IFD1024

Features you need, Prices you want.

Full-Spectrum, Cinema Quality Color

With Daylight LED bulbs, Ikan's IFD1024 is a powerful flood light that lets you enjoy soft, beautiful light and excellent color purity in just about any shooting scenario. This is the LED light you've been looking for.

Easy-to-Adjust Light Intensity

With a touch-sensitive digital display, a dimmer knob, and a remote control, you have options when it comes to adjusting the light intensity. The IFD1024 puts you in control so you can get the perfect lighting for your shot every time.

Exceptional Quality

As the IFD1024 light comes equipped with an AB to V-Mount pro battery plate, barn doors with intensifiers, diffuser, power supply, remote control, and yoke mount, it is an exceptional value.

What's Included

1 x IFD1024 Light

- 1 x AB Mount (Attached)
- 1 x AB to V-Mount Adapter
- 1 x Diffuser
- 1 x Power Supply
- 1 x Remote Control
- 1 x Yoke

IFD1024 Lights Available in Multiple Kits

IFD1024-2PT-KIT IFD2511 IFD1024-KIT IFD2115

Creations	
Specifications	
Beam Angle	50°
Brightness	3′ / 10543 lux mn 100K / 5600K(±100K)
Build Material	Heavy Duty Plastic
Color Temperature	5600K (±100K)
Control	Local Knob & Touchscreen
Cooling System	Passive Heat Sync
Dimming	10-100%
Fixture Size	14" x 14" x 2.75"
Fixture Weight	6 lbs
Focusing	N/A
Head Type	Daylight
Lens	60° Lens
Light Source	1024 0.06w LED @5600K
Mount	Yoke
Operating Wattage	82 w @ 120v/60Hz
Power Supply	12v @ 6.66 Amp
Rating	120v @ 60 Hz
Shipping Weight	11.2 lbs
Shipping Dimensions	17.75" x 19.5" x 5"

Optional Accessories

C-2KA-KIT C-2KS-KIT PWRGP-1 ID500-PS ID500-RC CH1546	AB Mount Pro Power System V-Mount Portable Pro Power System Power Grip Power Supply for ID500/IB500 Remote Control for ikan Lights Chimera for IER546/IED576
CH1546	Chimera for IFB546/IFD576

Photometrics





