

J100-JIB-KIT

J100 Fluid Arm Jib with Tripod & Dolly (*E-Image*)

ONE SHEET

Overview

When the script calls for fluid and precise craning camera movements, don't sacrifice your camera work due to the inability to get a traditional jib on location. E-Image's Huntsman J100 jib provides stable and reliable camera control in a highly portable jib package. Built from precision CNC machined parts and rock-solid pure carbon fiber tubing, the Huntsman is unnaturally lightweight yet as strong as steel. An advanced dampening system on the tilt and pan axis allows the operator to customize the jib's action so it feels natural to the touch. Furthermore, a unique head design provides numerous methods of attaching the camera to the jib for movements that require an alternative to the standard.



J100-JIB-KIT | J100 Fluid Arm Jib with Tripod & Dolly (*E-Image*) | **UPC Code:** 847983021307

Special Features

- Innovative fluid jib arm with all necessary accessories
- Fluid dampening system for both pan and tilt
- Tilt angle of lens can be adjusted in real time
- Multiple shooting modes
- Multiple mounting points for lights and other accessories
- Durable “plum blossom” locking knob
- Includes adjustable tripod and studio dolly

Recommended For

- Field Videography
- Studio Videography

ikan

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com



www.facebook.com/ikanseeit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

J100-JIB-KIT

Features you need, Prices you want.

Fluid Dampening System

The J100 has extremely smooth movement provided by the 0-3 grades of fluid dampening adjustment for both the pan and tilt axis.

Real Time Adjustment of Tilt Angle

Camera operators may easily adjust the tilt angle of the lens in real time.

Always Focus on the Subject

By adjusting the jib's arm angle, you can consistently maintain focus on the subject.

What's Included

- 1 x 771CT Tripod
- 1 x Counterweight
- 1 x EI-7004C Dolly
- 1 x J100 Fluid Arm Jib
- 1 x Long Plate Adapter with Bowl Mount
- 1 x Operation Handle
- 1 x Soft Travel Case

Optional Accessories

- DH5e DH5e 5" 4K Touch Screen HDMI On-Camera Monitor
- DH7 DH7 7" 4K HDMI On-Camera Monitor
- VXF7 VXF7 7" 4K HDMI/3G-SDI On-Camera Monitor
- IK-RSR3 3" Camera Riser
- IK-RSR6 6" Hi-Hat Riser
- GH03F GH03F Flat Base Pro Fluid Video Head
- BZ400 Blitz 400 Wireless Zero Delay HD Video System
- BZ400-PRO Blitz 400 PRO Wireless Zero Delay HD Video System
- BZ1000-PRO Blitz 1000 PRO Wireless Zero Delay HD Video System

J100 Fluid Arm Specifications

Payload	33 lbs
Weight	9.9 lbs
Extended Length	88.6 In.
Collapsed Length	36.2 In.
Max Working Radius	57.1 In.
Grades of Tilt / Drag	0-3
Tilt Range	-22° ~ +55°

771CT Tripod Specifications

Height Range	8.75 - 71 In.
Transport Length	27 In.
Bowl Size	75mm
Payload	55 lbs
Spreader	None
Weight	6.4 lbs

EI-7004C Specifications

Payload	132.28 lbs
Footprint Diameter	39.37 In.
Weight	6.4 lbs

Shipping Specifications Box 1

Shipping Dimensions	41.7 x 15.7 x 9.1 In.
---------------------	-----------------------

Shipping Specifications Box 2

Shipping Dimensions	30 x 8.3 x 8.63 In.
---------------------	---------------------

Shipping Specifications Box 3

Shipping Dimensions	22.8 x 9.1 x 9.8 In.
---------------------	----------------------

Shipping Specifications Box 4

Shipping Dimensions	10.6 x 6.7 x 9.8 In.
Shipping Weight (Total)	59.95 lbs

