

LBX15

Lyra 1 x 1 XL Bi-Color Studio Light with DMX Control

ONE SHEET

Overview

Ikan's Lyra Studio DMX brand of soft lights feature high CRI Chip LEDs paired with a soft panel giving you a very soft, wrapping light. Its Bi-color adjustability from 3200K-5600K is great for any light setup. Also, the brightness of the light is consistent across all color temperatures. The beam angle of the light is a wide 110°, making it possible to light a large area with a single fixture. The best thing about a Lyra soft light is the nice, clean shadow you get from the light itself. The heavy duty yoke and baby 5/8" and junior 1-1/8" Combo Pin allows you to attach to any stand or use in any studio.



LBX15 | Lyra 1 x 1 XL Bi-Color Studio Light with DMX Control | **UPC Code:** 847983021970

Special Features

- High CRI Chip LEDs paired with ½ Stop Soft Diffusion Panel
- Bi-Color Adjustable from 3200K-5600K
- Bright, Consistent Light Across all Color Temperatures
- Beam Angle of Soft Panel 110°
- Clean, Single Shadows without Artifacts
- DMX In and Out

Recommended For

- Studio Use
- Field Use



www.facebook.com/ikanseit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

ikan

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com

LBX15

Features you need, Prices you want.

High CRI Chip LEDs

The high CRI Chip LEDs give you a strong output allowing for very bright diffused light.

Bi-Color Adjustable

The LBX15 has a bi-color adjustable range from 3200K-5600K.

Consistent Light

The Lyra light gives you a very consistent bright light with all color temperatures.

110° Beam Angle

A wide beam angle gives you plenty of soft light.

Clean Single Shadow

The single shadows give you a more natural shot.

Combo Pin

With a Baby 5/8" and Junior 1-1/8" Combo pin allows for the use of any grip stand.

Quick Set Disk Locking

The quick set disk locking system allows you to position the light when up on the grid.

Single Knob Control

Users can easily adjust the brightness, color, or DMX on the fly by using the single control knob on the lights.

New LED Readout Screen

The new, bright LED readout gives you a quick reference of the light's output.

What's Included

- 1 x Lyra Bi-Color DMX Studio Light
- 1 x Power Cord
- 1 x Power Supply
- 1 x Yoke Mount

Fixture Specifications

Head Type	Bi-Color 3200K-5600K
Lens	½ Stop Soft Diffusion
Beam Angle	110°
Control/Dimming	DMX & Local Knob Control
Build Material	Metal & Plastic Shell
Cooling System	Active Cooling
Yoke	Baby 5/8" - Junior 1 1/8" Combo Pin
Fixture Size	24 x 5 x 26 In.
Fixture Weight	19 lbs

Electrical Specifications

Power Supply	Input: 100-220VAC Output: 27.2VDC
Fixture Power Consumption	212 Watts

Shipping Specifications

Shipping Dimensions	28 x 7 x 32 In.
Shipping Weight	29 lbs

Optional Accessories

KCP-703	Stage Clamp with 16mm Stud
ROLLR-STND10	2-Stage Roller Stand 10 ft 6 in
SW-04	Safety Wire
IDX-096	96 Channel DMX Console

Photometrics

LBX15 - Lyra Bi-Color Soft Light **3200K**

110°	FC	540	226	117	67	50	37	29	23	19	15
	FEET	2'	4'	6'	8'	10'	12'	14'	16'	18'	20'
110°	LUX	5812	2432	1259	721	538	398	312	247	204	161
	METERS	0.6M	1.2M	1.8M	2.4M	3M	3.6M	4.2M	4.8M	5.4M	6.1M

LBX15 - Lyra Bi-Color Soft Light **5600K**

110°	FC	592	244	127	73	53	40	31	25	20	16
	FEET	2'	4'	6'	8'	10'	12'	14'	16'	18'	20'
110°	LUX	6372	2626	1367	785	570	430	333	269	215	172
	METERS	0.6M	1.2M	1.8M	2.4M	3M	3.6M	4.2M	4.8M	5.4M	6.1M

