## Lyra 1 x 2 Bi-Color Studio Light with DMX Control

## **ONE SHEET**

## **Overview**

Ikan's Lyra Studio DMX Brand of soft lights have high CRI chip LEDs paired with a soft panel, giving you a very soft, wrapping light. Its Bi-Color adjustability from 3200K-5600K is great for any light setup. Also, the brightness of the light is consistent across all color temperatures. The beam angle of the light is a wide 110°, making it possible to light a large area with a single fixture. The best thing about a Lyra Soft Light is the nice clean shadow you get from the light itself. The heavy duty yoke and Baby 5/8" and Junior 1 1/8" Combo Pin allows you to attach to any stand or use in any studio configurations, The quick set disk locking system allows professionals to lock the light in place when aiming the fixture. The large yellow knob on the back allows you to control the light with a few simple clicks. You can control the brightness, color temperature, and the DMX Channel, making adjustments as needed. The LED readout gives you the ability to have precise measurements. The 1 x 2 LED Soft Panel is an extremely bright, soft light that gives the end user the control to light sets or any scene on a stage. These lights are great for any talk show or broadcast news shows.



#### LBX20 | Lyra 1 x 2 Bi-Color Studio Light with DMX Control | UPC Code: 847983021994

## **Special Features**

- High CRI Chip LEDs paired with ½ Stop Soft Diffusion Panel
- Bi-Color Adjustable from 3200K-5600K
- Bright, Consistent Light Across all Color Temperatures
- Beam Angle of Soft Panel 110°
- Clean, Single Shadows without Artifacts
- DMX In and Out

## **Recommended For**

- Studio Use
- Field Use



www.facebook.com/ikanseeit

www.twitter.com/ikancorp

www.vimeo.com/ikancorp

www.youtube.com/ikancorp



# LBX20

#### **High CRI Chip LEDs**

The high CRI Chip LEDs give you a strong output allowing for very bright diffused light.

#### **Bi-Color Adjustable**

The LBX20 has a bi-color adjustable range from 3200K-5600K.

#### **Consistent Light**

The Lyra light gives you a very consistent bright light with all color temperatures.

#### 110° Beam Angle

A wide beam angle gives you plenty of soft light.

#### **Clean Single Shadow**

The single shadows give you a more natural shot.

#### Combo Pin

With a Baby 5/8" and Junior 1-1/8" Combo pin allows for the use of any grip stand.

#### **Quick Set Disk Locking**

The quick set disk locking system allows you to position the light when up on the grid.

#### Single Knob Control

Users can easily adjust the brightness, color, or DMX on the fly by using the single control knob on the lights.

#### New LED Readout Screen

The new, bright LED readout gives you a quick reference of the light's output.

#### What's Included

1 x Lyra Bi-Color DMX Studio Light

- 1 x Power Cord
- 1 x Power Supply
- 1 x Yoke Mount



Fixture Specifications					
Head Type	Bi-Color 3200K-5600K				
Lens	1/2 Stop Soft Diffusion				
Beam Angle	110°				
Control/Dimming	DMX & Local Knob Control				
Build Material	Metal & Plastic Shell				
Cooling System	Active Cooling				
Yoke	Baby 5/8" - Junior 1 1/8" Combo Pin				

Features you need, Prices you want.

Electrical Specifications					
Power Supply	Input: 100-220VAC				
	Output: 27.2VDC				
Fixture Power Consumption	205 Watts				

20 x 5 x 29 ln.

18 lbs

Shipping Specifications					
Shipping Dimensions	26 x 7 x 31 ln.				
Shipping Weight	25 lbs				

#### **Optional Accessories**

**Fixture Size** 

**Fixture Weight** 

KCP-703	Stage Clamp with 16mm Stud				
ROLLR-STND10	2-Stage Roller Stand 10 ft 6 in				
SW-04	Safety Wire				
IDX-096	96 Channel DMX Console				

#### **Photometrics**

LBX20 - Lyra Bi-Color Soft Light 3200K

110°	FC FEET	586 <mark>-</mark> 2'	215 <mark> </mark> 4'	113 	65 	48  10'	36  12'	29 14'	23 	19 	15 
<mark>110°</mark>	LUX METERS	5812 0.6M	2432 1.2M	1259 1.8M	721 	538 	398 	312 4.2M	236 4.8M	182 	150  6.1M
LBX20 - Lyra Bi-Color Soft Light 5600K											
110°	FC FEET	652  2'	240 <mark> </mark> 4'	127 <mark>-</mark> 6'	74 <mark> </mark> 8'	54 <mark>-</mark> 10'	41 <mark> </mark> 12'	32 14'	25 16'	20 <mark>-</mark> 18'	16 
110°	LUX METERS	7018  0.6M	2583  1.2M	1367   1.8M	796 <mark>-</mark> 2.4M	581 	441 <mark>-</mark> 3.6M	344 4.2M	269  4.8M	215 	172  6.1M

