L5-12000E

12kW HMI Fresnel Kit (Lightstar)

ONE SHEET

Overview

The Lightstar 12kW HMI Freshnel Kit delivers the color of the sun to your fingertips! From spot to flood lighting, it provides all the necessary daylight control. The kit's heavy-duty aluminum alloy fixture allows heat to dissipate quickly. The Fresnel lens lets you control the spread of the light while the onboard dimming feature adjusts the level of brightness. With its durable coating and industrial connectors, the 7 meter long Head to Ballast cable enables it to endure the most demanding environments with ease. The 12,000/6000 Watt Electronic Ballast can handle Flicker free shooting up to 10,000 fps. Best of all, it is much smaller and lighter than the standard magnetic ballast!



LS-12000E | 12kW HMI Fresnel Kit (Lightstar) | UPC Code: 847983020447

Special Features

- Aluminum Alloy Light Fixture
- 12000/6000 Watt Electronic Ballast
- 15 Meter Head to Ballast Cable
- Barn Doors Included

Recommended For

- Studio Lighting
- Field Lighting



www.facebook.com/ikanseeit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp



www.ikancorp.com

1.713.272.8822

sales@ikancorp.com



Aluminum Alloy Design

The heat fixture features a heavy-duty aluminum body for quick heat release.

Efficient Beam Output

The fresnel lens makes it easy to create a clean, sharp edge through the beam.

Powerful Electronic Ballast

The 12,000/6000 Watt Electronic Ballast provides Flicker-free shooting up to 10,000 fps.

Head to Ballast Cable

The heavy-duty 15 meter ballast cable extends far enough for you to place the light away from the ballast.

Increase Bulb Life

The 12,000/6000 Watt Electronic Ballast increases bulb life by at least 20% when compared to magnetic ballast.

What's Included

- 1 x 12kW/6kW Electronic Ballast
- 1 x 12kW HMI Fresnel Light Fixture
- 1 x 15 Meter Head to Ballast Cable
- 1 x Barn Doors
- 1 x Gel Holder
- 1 x Yoke

Features you need, Prices you want.

LS-12000E Fixture Specifications	
Head Type	HMI Fresnel 12000W
Lens Size	Fresnel 19.7" Lens
Lamp Base	12000W/160V-G38
Beam Angle	9°-60°
Control/Dimming	50%-100%
Focusing	Knob Controlled
Build Material	Aluminum
Cooling System	Air Cooled
Yoke	Cast Aluminum with 1 1/8" Pin
IP Class	IP23
Fixture Size	27 x 34 x 41 in.
Fixture Weight	85 lbs

Electronic Ballast Specifications		
Power Supply	Electronic Ballast 12000/6000W	
Input Voltage	180-250VAC	
Electronic Ballast Size	16.7 x 10.4 x 20.1 in.	
Electronic Ballast Weight	79 lbs	

Shipping Specifications	
Shipping Dimensions Box 1	29 x 37 x 47 in.
Shipping Dimensions Box 2	24 x 15 x 25 in.
Shipping Weight	175 lbs

Optional Accessories

KCP-703 Stage Clamp with 16mm Stud SW-04 Safety Wire





