

LS-1812E

18kW/12kW HMI Fresnel Kit (*Lightstar*)

ONE SHEET

Overview

The Lightstar 18kW/12kW HMI Fresnel Kit delivers the color of the sun to your fingertips! From spot to flood lighting, it provides all the necessary daylight control. The kit's heavy-duty aluminum alloy fixture allows heat to dissipate quickly. The Fresnel lens lets you control the spread of the light while the onboard dimming feature adjusts the level of brightness. With its durable coating and industrial connectors, the 7 meter long Head to Ballast cable enables it to endure the most demanding environments with ease. The 18kW/12kW Electronic Ballast can handle Flicker free shooting up to 10,000 fps. Best of all, it is much smaller and lighter than the standard magnetic ballast!



LS-1812E | 18kW/12kW HMI Fresnel Kit (*Lightstar*) | UPC Code: 847983021765

Special Features

- Aluminum Alloy Light Fixture
- 18000/12000 Watt Electronic Ballast
- 15 Meter Head to Ballast Cable
- Barn Doors Included

Recommended For

- Studio Lighting
- Field Lighting

ikan

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com



www.facebook.com/ikanseit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

LS-1812E

Features you need, Prices you want.

Aluminum Alloy Design

The heat fixture features a heavy-duty aluminum body for quick heat release.

Efficient Beam Output

The fresnel lens makes it easy to create a clean, sharp edge through the beam.

Powerful Electronic Ballast

The 18,000/12,000 Watt Electronic Ballast provides Flicker-free shooting up to 10,000 fps.

Head to Ballast Cable

The heavy-duty 15 meter ballast cable extends far enough for you to place the light away from the ballast.

Increase Bulb Life

The 18,000/12,000 Watt Electronic Ballast increases bulb life by at least 20% when compared to magnetic ballast.

What's Included

- 1 x 18kW/12kW Electronic Ballast
- 1 x 18kW/12kW HMI Fresnel Light Fixture
- 1 x 15 Meter Head to Ballast Cable
- 1 x Barn Doors
- 1 x Gel Holder
- 1 x Yoke

LS-12000E Fixture Specifications

Head Type	HMI Fresnel 18000/12000W
Lens Size	Fresnel 24.6" Lens
Lamp Base	12000W/160V-G38
Beam Angle	15°-56°
Control/Dimming	50%-100%
Focusing	Knob Controlled
Build Material	Aluminum
Cooling System	Air Cooled
Yoke	Cast Aluminum with 1 1/8" Pin
IP Class	IP23
Fixture Size	33 X 37 X 48 in.
Fixture Weight	159 lbs

Electronic Ballast Specifications

Power Supply	Electronic Ballast 18kW/12kW
Input Voltage	190-250VAC
Electronic Ballast Size	19.9 x 12 x 21.1 in.
Electronic Ballast Weight	124.7 lbs

Shipping Specifications

Shipping Dimensions Box 1	37 x 33 x 30 in.
Shipping Dimensions Box 2	24 x 15 x 25 in.
Shipping Weight	295 lbs

Optional Accessories

KCP-703
SW-04

Stage Clamp with 16mm Stud
Safety Wire

