

LS-4000PE

2500/4000 Watt HMI PAR Kit (*Lightstar*)

ONE SHEET

Overview

The Lightstar 2500/4000 Watt PAR Light Kit with electronic ballast delivers crisp, clear and balanced daylight. A hot light won't be an issue as the aluminum alloy chassis provides quick heat release. It also comes with a five lens set that allows you to focus in any direction to capture the best shot. With its durable coating and industrial connectors, the 7 meter long head to ballast cable enables it to endure the most demanding environments with ease. The electronic ballast can handle flicker free shooting up to 10,000 fps. Best of all, it is much smaller and lighter than the standard magnetic ballast! Along with the included barn doors, this light is perfect for your day-to-day production needs.



LS-4000PE | 2500/4000 Watt HMI PAR Kit (*Lightstar*) | UPC Code: 847983020409

Special Features

- Corrosion resistant aluminum alloy light fixture
- Easily operated with adjustable focusing knob
- 7 Meter head to ballast cable
- Electronic ballast included
- 5 Lens set for Spot, Narrow flood, Flood, Super Flood, and Frost
- Barn doors included

Recommended For

- Field Lighting
- Studio Lighting



www.facebook.com/ikanseeit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

ikan

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com

LS-4000PE

Features you need, Prices you want.

Aluminum Alloy Fixture

The heavy-duty aluminum alloy light fixture enables head to dissipate much faster

5 Lens Set

The five lens set provides all the control you need for any PAR light. It includes these types of lenses: Spot, Flood, Narrow Flood, Super Flood, and Frost

High Output Efficiency

The output efficiency is greater than 90% with special parabolic reflector.

Barn Doors Included

The large barn doors allow you to easily shape and cut the light as needed.

Powerful Electronic Ballast

The electronic ballast provides flicker-free shooting up to 10,000 fps.

Head to Ballast Cable

The heavy duty 7 meter ballast cable extends far enough for you to place the light away from the ballast.

What's Included

- 1 x 2500/4000 Watt Electronic Ballast
- 1 x 2500/4000W HMI PAR Light
- 1 x 5 Lens Set
- 1 x 7-Meter Heavy Duty Head to Ballast Cable
- 1 x Barn Door
- 1 x Gel Holder
- 1 x Yoke

LS-4000PE Fixture Specifications

Head Type	HMI PAR 2500/4000W
Lens Size	Fresnel 13.6" Lens
Lamp Base	2500W/115V/G38 or 4000W/200V/G38
Beam Angle	5°- 41°
Control/Dimming	50%-100%
Focusing	Knob Controlled
Build Material	Aluminum
Cooling System	Air Cooled
Yoke	Cast Aluminum w/ 1 1/8" Pin
IP Class	IP23
Fixture Size	33.1 x 20.5 x 22 in.
Fixture Weight	55 lbs

Electronic Ballast Specifications

Power Supply	Electronic Ballast 2500/4000W
Input Voltage	24VDC/100-240VAC
Electronic Ballast Size	17.7 x 10.2 x 14.2 in.
Electronic Ballast Weight	43.7 lbs

Shipping Specifications

Shipping Dimensions Box 1	23 x 22 x 24 in.
Shipping Dimensions Box 2	22 x 15 x 20 in.
Shipping Weight	109 lbs

Optional Accessories

- KCP-703** Stage Clamp w/ 16mm Stud
- LS-HB7** Head to Ballast Cable 23' (7m) (*Lightstar*)

