

LS-575SPX

575 Watt HMI Super Spot Kit (*Lightstar*)

ONE SHEET

Overview

The Lightstar Super Spot Light HMI gives the user a clean, clear Daylight balanced light. The aluminum alloy chassis allows for quick heat release.

The 575 Watt compact ballast attaches directly to the yoke of the light for a nice, compact look. Additionally, a 4-Foot ballast cable can easily connect from the light fixture to the ballast.

To top it off, the included barn doors equip the LS-575SPX with all of the accessories needed for any lighting production!



LS-575SPX | 575 Watt HMI Super Spot Kit (*Lightstar*) | UPC Code: 847983015115

Special Features

- Aluminum Alloy Light Fixture
- 575 Watt/1200 Watt Electronic Ballast with dimming capabilities that attaches to the yoke of the light
- 4-Foot Ballast Cable
- 5 Lens set for Spot, Narrow Flood, Flood, Super Flood, and Frost
- Barn doors included

Recommended For

- Studio Lighting
- Field Lighting
- Specialty Lighting

ikan

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com



www.facebook.com/ikanseeit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

LS-575SPX

Features you need, Prices you want.

Aluminum Alloy Fixture

The LS-575SPX Light features a heavy-duty aluminum body for quick heat release.

575 Watt Electronic Ballast

Dimming the light is extremely easy with 575-Watt electronic ballast.

4-Foot Ballast Cable

The 4-Foot head cable can easily attach from the light fixture to the ballast.

5 Lens Set

The five lens set provides all the control you will need for any Par light. It includes these different types:

- Spot
- Flood
- Narrow Flood
- Super Flood
- Frost

Barn Doors Included

The large barn doors allow you to easily shape and cut the light as needed.

What's Included

- 1 x 575W HMI Super Spot Kit
- 1 x Barn Doors
- 1 x 575 Electronic Ballast
- 1 x 4' Head to Ballast Cable
- 1 x Yoke
- 1 x Gel Holder
- 1 x 5 insert Lens System (1x Spot, 1x Flood, 1x Narrow Flood, 1x Super Flood, 1x Frost)

Specs

Head Type	LS-575SPX
Rating	HMI PAR 575W
Light Source	575 Watt
Power Supply	Electronic Ballast
Voltage Range	95V - 120V
Lamp Base / Bulb	HMI / 120V / G22
Dimming	50-100%
Lens Size	250mm or 9.8"
Focusing	5 Insert Lens System
No Lens	5°
Spot Beam Angle	9°
Narrow Flood Beam	11° x 22°
Flood Beam Angle	21° x 42°
Super Flood Beam Angle	42°
Frost Beam Angle	35°
Cooling System	Air-Cooled
Yoke	Cast Aluminum w/ 11/8" Pin
IP Class	IP23
Fixture Size	18.5 x 10.5 x 12.5 In.
Fixture Weight	18 lbs
Shipping Dimensions	22 x 12 x 12 In. 55.88 x 30.48 x 30.48 cm
Shipping Weight	30 lbs / 13.6 kg

LS-575SPX Photometrics

	Spot	Narrow Flood	Flood	Super Flood
10 Ft	82800 LUX	33600 LUX	9500 LUX	7200 LUX
	7692.3 FC	3121.5 FC	882.5 FC	668.9
16 Ft	29900 LUX	12000 LUX	3400 LUX	2600 LUX
	2777.8 FC	1114.8 FC	315.8 FC	241.5 FC
32 Ft	7500 LUX	3040 LUX	850 LUX	650 LUX
	696.7 FC	282.4 FC	78.9 FC	60.3 FC

Accessories

- KCP-703** Stage Clamp w/ 16mm Stud
- SW-04** Safety Wire
- CV600** Chrome Exposure / Spectrometer from UPRtek



ikan

Houston, Texas

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com