

LS-575TE

575 Watt HMI Fresnel Kit (*Lightstar*)

ONE SHEET

Overview

The Lightstar 575 Watt HMI Fresnel Kit delivers the color of the sun to your fingertips! From spot to flood lighting, it provides all the necessary daylight control. The kit's heavy-duty aluminum alloy fixture allows heat to dissipate quickly. The fresnel lens lets you control the spread of the light with on-board dimming feature adjusts the level of brightness.

With its durable coating and industrial connectors, the 8-Meter long Head to Ballast cable enables it to endure the most demanding environments with ease. The 575/1200W Electronic Ballast can handle Flicker-free shooting up to 10,000 fps. Best of all, it is much smaller and lighter than the standard magnetic ballast!



LS-575TE | 575 Watt HMI Fresnel Kit (*Lightstar*) | UPC Code: 847983015092

Special Features

- Aluminum Alloy Light Fixture
- Efficient Beam Output with Glass Fresnel Lens
- 8 Meter Head Ballast Cable
- 575 Watt/1200 Watt Electronic Ballast

Recommended For

- Studio Lighting

ikan

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com



www.facebook.com/ikanseeit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

LS-575TE

Features you need, Prices you want.

Aluminum Alloy Fixture

The heavy-duty aluminum alloy light fixture enables heat to dissipate much faster.

Efficient Beam Output

The fresnel lens provides a clean, sharp edge beam.

Head to Ballast Cable

The heavy-duty 8-Meter ballast cable extends far enough for you to place the light away from the ballast.

Powerful Electronic Ballast

The 575/1200W Electronic Ballast provides Flicker-free shooting up to 10,000 fps.

What's Included

- 1 x 575W HMI Fresnel Light Fixture
- 1 x Barn Doors
- 1 x 575/1200W Electronic Ballast
- 1 x 8 meter Head to Ballast Cable
- 1 x Yoke
- 1 x Gel Holder

Accessories

- KCP-703 Stage Clamp w/ 16mm Stud
- SW-04 Safety Wire
- IDX-096 96 Channel DMX Console
- CV600 Color Meter

LS-575PE Specifications

Head Type	LS-575TE
Rating	HMI Fresnel 575W
Light Source	Metal Halide 575W / SE
Power Supply	Electric Ballast 575w / 1200
Voltage Range	95V - 120V
Lamp Base / Bulb	HMI 575 / 95V / G22
Dimming	50-100%
Lens Size	Fresnel 5.1" Lens
Focusing	Knob Controlled
Beam Angle	8-60
Cooling System	Air Cooled
Yoke	Cast Aluminum w/ 1 1/8" Pin
IP Class	IP23
Fixture Size	18.5 x 10.5 x 12.5 In.
Fixture Weight	18 lbs
Shipping Dimensions	24 x 20 x 12 In. / 60.96 x 50.8 x 30.48 cm
Shipping Weight	41 lbs / 18.5 kg

LS-575TE Photometrics

	8 Degrees	60 Degrees
13 Feet	15300 LUX	1875 LUX
	1421.4 FC	174.1 FC
16 Feet	9800 LUX	1200 LUX
	910.4 FC	111.4 FC
19 Feet	6800 LUX	823 LUX
	631 FC	76.4 FC

