LS-6000PE

6000 Watt HMI PAR Kit (Lightstar)

ONE SHEET

Overview

The Lightstar 6000 Watt PAR Light Kit with electronic ballast delivers a crisp, clear and balanced daylight. A hot light won't be an issue as the aluminum alloy chassis provides quick heat release. It also comes with a five lens set that allows you to focus in any direction to capture the best shot. With its durable coating and industrial connectors, the 7 meter long head to ballast cable enables it to endure the most demanding environments with ease. The electronic ballast can handle flicker free shooting up to 10,000 fps. Best of all, it is much smaller and lighter than the standard magnetic ballast! Along with the included barn doors, this light is perfect for your day-to-day production needs.



LS-6000PE | 6000 Watt HMI PAR Kit (Lightstar) | UPC Code: 847983020430

Special Features

- Corrosion resistant aluminum alloy light fixture
- Easily operated with adjustable focusing knob
- 7 Meter head to ballast cable
- Electronic ballast included
- 5 Lens set for Spot, Narrow flood, Flood, Super flood, and Frost
- Barn doors included

ikan

Recommended For

- Field Lighting
- Studio Lighting



www.facebook.com/ikanseeit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com



Aluminum Alloy Fixture

The heavy-duty aluminum alloy light fixture enables head to dissipate much faster

5 Lens Set

The five lens set provides all the control you need for any PAR light. It includes these types of lenses: Spot, Flood, Narrow Flood, Super Flood, and Frost

High Output Efficiency

The output efficiency is greater than 90% with special parabolic reflector.

Barn Doors Included

The large barn doors allow you to easily shape and cut the light as needed.

Powerful Electronic Ballast

The electronic ballast provides flicker-free shooting up to 10,000 fps.

Head to Ballast Cable

The heavy duty 7 meter ballast cable extends far enough for you to place the light away from the ballast.

What's Included

- 1 x 5 Lens Set
- 1 x 6000 Watt Electronic Ballast
- 1 x 600W HMI PAR Light
- 1 x 7-Meter Heavy Duty Head to Ballast Cable
- 1 x Barn Doors
- 1 x Gel Holder
- 1 x Yoke

Features you need, Prices you want.

LS-6000PE Fixture Specifications	
Head Type	HMI PAR 6000W
Lens Size	Fresnel 17" Lens
Lamp Base	6000W/123V/G38
Beam Angle	7°- 40°
Control/Dimming	50%-100%
Focusing	Knob Controlled
Build Material	Aluminum
Cooling System	Air Cooled
Yoke	Cast Aluminum w/ 1 1/8" Pin
IP Class	IP23
Fixture Size	37.5 x 24.4 x 27.8 in.
Fixture Weight	88 lbs

Electronic Ballast Specifications		
Power Supply	Electronic Ballast 6000W	
Voltage Range	180-250VAC	
Electronic Ballast Size	14.2 x 10.2 x 17.7 in	
Electronic Ballast Weight	50.7 lbs	

Shipping Specifications	
Shipping Dimensions Box 1	37 x 33 x 28 in.
Shipping Dimensions Box 2	24 x 15 x 25 in.
Shipping Weight	152 lbs

Optional Accessories

KCP-703 Stage Clamp w/ 16mm Stud

LS-HB7 Head to Ballast Cable 23' (7m) (Lightstar)





