

LSC-005

4000 Watt HMI Fresnel Head (*Lightstar*)

ONE SHEET

Overview

The Lightstar 4000 Watt HMI Fresnel Head provides the powerful light you need when the sun isn't working in your favor. From spot to flooding lighting, it provides all the necessary daylight control. The aluminum alloy fixture allows heat to dissipate quickly. The fresnel lens lets you control the spread of the light while the on-board dimming feature adjusts the level of brightness.



LSC-005 | 4000 Watt HMI Fresnel Head (*Lightstar*) | UPC Code: 847983020232

Special Features

- Aluminum Alloy Light Fixture
- Efficient Beam Output with Glass Fresnel Light
- Barn Doors Included

Recommended For

- Studio Lighting
- Field Lighting
- Specialty Lighting

ikan

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com



www.facebook.com/ikanseeit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

LSC-005

Features you need, Prices you want.

Aluminum Alloy Design

The LSC-005 light features a heavy-duty aluminum body for quick heat release.

Efficient Beam Output

The Fresnel lens makes it easy to create a clean, sharp edge through the beam.

What's Included

- 1 x 4000W HMI Fresnel Light Fixture
- 1 x Barn Doors
- 1 x Yoke
- 1 x Gel Holder

Optional Accessories

- KCP-703** Stage Clamp with 16mm Stud
- SW-04** Safety Wire
- CV600** Digital LED Light Meter with Exposure

Specifications

Beam Angle	7° to 60°
Build Material	Aluminum
Color Temperature	5600K
Cooling System	Air Cooled
Fixture Size	31 x 24 x 18.9 in.
Fixture Weight	56 lbs
Focusing	Knob Control
Head Type	HMI Fresnel 4000W
IP Class	IP23
Lamp Base	4000W / 200V / G38
Lens Size	11.8" Fresnel
Yoke	Cast Aluminum with 1 1/8" Pin

Shipping Specifications

Shipping Dimensions	23 x 22 x 24 in.
Shipping Weight	60 lbs

Photometrics

7°	LUX	21250	9445	5313
	METERS	10M	15M	20M
60°	LUX	1750	778	438
	METERS	10M	15M	20M
7°	FC	1974.2	877.5	493.6
	FEET	29.5'	39'	49'
60°	FC	162.6	72.3	40.7
	FEET	29.5'	39'	49'

