

LSC-008

18kW/12kW Watt HMI Fresnel Head (*Lightstar*)

ONE SHEET

Overview

The Lightstar 18,000 /12,000 Watt HMI Fresnel Head provides the powerful light you need when the sun isn't working in your favor. From spot to flooding lighting, it provides all the necessary daylight control. The aluminum alloy fixture allows heat to dissipate quickly. The fresnel lens lets you control the spread of the light while the on-board dimming feature adjusts the level of brightness.



LSC-008 | 18KW/12KW Watt HMI Fresnel Head (*Lightstar*) | UPC Code: 847983020324

Special Features

- Aluminum Alloy Light Fixture
- Efficient Beam Output with Glass Fresnel Light
- Barn Doors Included

Recommended For

- Studio Lighting
- Field Lighting
- Specialty Lighting

ikan

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com



www.facebook.com/ikanseeit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

LSC-008

Features you need, Prices you want.

Aluminum Alloy Design

The LSC-008 light features a heavy-duty aluminum body for quick heat release.

Efficient Beam Output

The Fresnel lens makes it easy to create a clean, sharp edge through the beam.

What's Included

- 1 x 18,000/12,000W HMI Fresnel Light Fixture
- 1 x Barn Doors
- 1 x Yoke
- 1 x Gel Holder

Optional Accessories

- KCP-703** Stage Clamp with 16mm Stud
- SW-04** Safety Wire
- CV600** Digital LED Light Meter with Exposure

Specifications

Beam Angle	15° to 56°
Build Material	Aluminum
Color Temperature	5600K
Cooling System	Air Cooled
Fixture Size	33 x 37 x 48 in.
Fixture Weight	159 lbs
Focusing	Knob Control
Head Type	HMI Fresnel 12000W
IP Class	IP23
Lamp Base	12000W / 160V / G38
Lens Size	24.6" Fresnel
Yoke	Cast Aluminum with 1 1/8" Pin

Shipping Specifications

Shipping Dimensions	37 x 33 x 30 in.
Shipping Weight	167 lbs

Photometrics

15°	LUX	11650	2200	635
	METERS	30M	75M	140M

56°	LUX	1650	300	85
	METERS	30M	75M	140M

15°	FC	1082.3	204.4	59
	FEET	98'	246'	459'

56°	FC	153.3	27.9	7.9
	FEET	98'	246'	459'

