Mylo Macro Bi-Color 3-Point LED Light Kit

ONE SHEET

Overview

The Mylo Macro Bi-Color LED light kit is designed for professionals who need solid lighting for an affordable price. This rugged field kit gives the user a professional appearance and performance in any lighting scenario. The 3 point light kit has everything that the working professional might need for an interview, music video, or short film.

The iLED6 Zoom ENG LED Light is designed and built for professional photographers, videographers and cinematographers who want a versatile, high quality and rugged LED light at an affordable price. The Daylight 6 3/4" x 2 3/4" LED light delivers field-tested reliability, solid construction, and all the features required for professional performance. The iLED6's features include energy efficient 5600K LEDs and a 30 to 60-degree angle that delivers reliable, consistent performance.

The Mylo Mini has all the same great features of its bigger brother just in a smaller compact package. The light can be powered by either AC power with the included power supply or DC power with two Sony "L" style batteries. The proven ikan barn doors are included to allow you to shape the light. With a maximum watts draw of 12.6W at 12 volts, the Mylo Mini LED Quarter x 1 light is equivalent to about a 300 watt light. The kit includes one stand bag, one light bag, and three compact stands.



MB-2Q1Z | Mylo Macro Bi-Color 3-Point LED Light Kit | UPC Code: 847983021260

Special Features

- High CRI 45° LEDs
- Bi-Color Adjustable from 3200K-5600K
- 50° Beam Angle
- Single Knob control for adjusting color and brightness
- New LED readout screen gives you precise control
- Battery powered by two included Sony "L" Style batteries
- MB4 Watts equivalent to 300 Watts incandescent light
- iLED6 Watts equivalent to 250 Watts incandescent light
- 2 Bags & 3 CP-v3 Stands are included

ikan

Recommended For

- Field & Studio Production
- Interviews



www.facebook.com/ikanseeit

www.twitter.com/ikancorp

www.vimeo.com/ikancorp

www.youtube.com/ikancorp

www.ikancorp.com 1.713.272.8822 sales@ikancorp.com

MB-2Q1Z

High CRI 45° LEDs

The High CRI LEDs give you a bright, consistent light.

Bi-Color Adjustable

The Bi-Color lights' adjustability ranges from 3200K-5600K, allowing professionals to incorporate it into any lighting scene.

Bright, Consistent Light

Mylo LEDs deliver a consistently bright light across all color temperature at all times.

50° Beam Angle

The Mylo LED's 50 degree beam angle provides a large amount of light all on its own.

Single Knob Control

A single knob makes it easy to adjust brightness & color.

New LED Readout

The brighter LED readout provides precise adjustments of light output.

Sony "L" Series Batteries

Battery flexibility is key when you're on-the-go. The Sony "L" style batteries are included.

Watts Equivalent

MB4 watts equivalent to 300 watts incandescent light, iLED6 watts equivalent to 250 watts incandescent light.

Kit Includes

The kit includes a stand bag, a kit bag, and 4 compact light stands.

What's Included

- 1 x iLED6 Light Fixture
- 2 x Mylo Mini Quarter x 1 Light Fixture
- 1 x Dual Charger
- 1 x IBG-312-3L
- 1 x Single Charger
- 3 x Barn Doors

ikan

- 3 x CP Light Stands
- 3 x Power Supply with Cable
- 5 x Sony "L" Style Batteries

Features you need, Prices you want.

MB-2Q1Z Specifications	
Beam Angle	50° / 30-60°
Cooling System	Passive Cooling
Dimming	Knob Control
Power Consumption	12.6 W/ 6W
Fixture Size	8 x 5 x 2 in. / 2.7 x 7.3 x 2.7 in.
Fixture Weight	1 lbs / 2 lbs
Head Type	Bi-Color 3200K-5600K (MB4)
	Daylight 5600K (iLED6)
Light Source	420 0.06 Watt LEDs / 1 10Watt LEDs
Power Supply	Input: 100-240 VAC
	Output: 12 VDC

Shipping Specifications	
Shipping Dimensions	28 x 10 x 10 in.
Shipping Weight	30 lbs

Optional Accessories

SM-301	Heavy Duty Shoe Mount
IBS-970	Sony "L" Series NP-F970 Compatible Battery
IBS-750	Sony "L" Series NP-F750 Compatible Battery
AB101	Anton/Bauer Power Tap Cable with Coaxial
EI-A07	Clamp with EI-A05 Stand Adapter
CP-STND-V3	Compact Light Stand Version 3

