

MS21

21.5" HD-SDI Monitor

ONE SHEET

Overview

The MS21 is a full-featured, high-definition monitor with an emphasis on precision color, luminance and 3D Lut.

The MS21 monitor accepts two HD-SDI signals for checking color between cameras, and easily switches between camera signals with the touch of a button on the front of the monitor. Further, each signal has it's own loop-through port for sharing with your director, editor or colorist. With same color representation between two or more units, this monitor is perfect for cooperative, color correction.



MS21 | 21.5" HD-SDI Monitor | UPC Code: 847983008155

Special Features

- Resolution of 1920x1080
- Dual HD-SDI Input with Loop Through
- Waveform / Vectorscope
- 8-16 Channel Audio Level Meter
- False Color, Peaking, & Clip Guides
- Closed Caption
- Time Code Display
- Tally Display
- Heavy Duty Metal Construction

Recommended For

- Studio
- On-Camera

 www.facebook.com/ikanseeit

 www.twitter.com/ikancorp

 www.vimeo.com/ikancorp

 www.youtube.com/ikancorp

ikan

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com

MS21

Features you need, Prices you want.

HD-SDI

The MS21 monitor accepts two HD-SDI signals for checking color between cameras, and easily switches between camera signals with the touch of a button on the front of the monitor. Further, each signal has its own loop-through port for sharing with your director, editor or colorist. With same color representation between two or more units, this monitor is perfect for cooperative, color correction.

Color Calibrated LCD

The MS21 LCD panel is calibrated to reproduce precise colors, while offering selectable color temperatures. Color temperature is one-touch user-adjusted. With higher video processing, color temperatures and gamma correction are applied to reproduce precise colors and gradients without stepping.

Waveform / Vectorscope

Monitor luminance and color range with waveform and vectorscope. Built-in to the MS21 monitor, waveform and vectorscope allow you to monitor exact levels in each color channel. Getting it right in the shot, saves you time in post production.

VESA Mount

The MS21 comes with a VESA mount on back for mounting on a stand, and can operate on 12v power when used in the field. You also get built-in speakers and a headphone jack for monitoring your audio.

What's Included

- 1 x MS21 Monitor
- 1 x CD Manual
- 1 x LCD Cleaning Cloth
- 1 x Power Cable
- 1 x Table Stand

Product Specs

Aspect Ratio	16:9
Back light	LED
Brightness	250 cd/m2
Build Material	Steel
Built-In Speaker	2W - 2 Stereo
Color	16.7M (8 Bit)
Color System	PAL / NTSC / SECAM (Auto-Detected)
Composite Input	1.0Vp-p (with sync), NTSC / PAL
Contrast Ratio	3000:1
Dimensions	19.9" x 13.7" x 2.3"
Display Technology	TFT LCD with LED Back light
HDMI	~1080p (60)
Input Voltage	AC (100-230v / 50/60Hz)
Inputs	(2) HD-SDI, (3) BNC Composite, (1) BNC Component
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Outputs	(2) HD-SDI, (3) BNC Composite, (1) BNC Component
Pixel Pitch	0.24825mm
Power Consumption	45w
Resolution	1920 x 1080
Screen Size	21.5"
Viewing Angle	178° horizontal / 178° vertical
Shipping Weight	17 lbs
Shipping Dimensions	23" x 14.3" x 5.7"

Optional Accessories

- PBK-A-X** Pro Battery Adapter Kit for AB w/ XLR P-Tap
- PBK-S-X** Pro Battery Adapter Kit for V-Mount w/ XLR P-Tap
- AB102** Anton Bauer Power Tap Cable w/ 4-Pin XLR
- IKW1** Wireless HD Transmitter & Receiver System (V-Mount)
- IKW1-A** Wireless HD Transmitter & Receiver System (AB Mount)

