# 

Mylo Soft Bi-Color 5-Point LED Light Kit

**ONE SHEET** 

### **Overview**

Ikan's Mylo Soft Bi-Color 3200K-5600K Half x 1 Field LED Light combines high CRI LED chips with a soft panel for a beautiful soft wrapping light. Its 3200K-5600K bi-color adjustability and high 95+ CRI LEDs provide high color fidelity with a constant brightness across all color temperatures for all lightning scenarios. The 110° beam angle makes it easy to light a large area with just one fixture. The MSB8 light is equivalent to a 450 watt incandescent soft light. Durability and versatility are key features of this impressive LED light. The heavy duty metal chassis and raised corners allow it to endure any harsh field environment while the strong, steel tension knobs on the yoke securely lock the light in place at all times. The Baby 5/8" and Junior 1 <sup>1</sup>/<sub>8</sub>" combo pin also allow you to attach or configure it in different ways. An AC power supply and two Sony "L" batteries for DC power come with this incredible light package. On the back, the large yellow button/knob allows you to adjust the light's brightness and color temperature with a few simple clicks. Ikan's reliable barn doors with intensifiers are included to shape the light as needed. The LED readout also provides very precise measurements.



MSB8-5PT-KIT | Mylo Soft Bi-Color 5 Point LED Light Kit | UPC Code: 847983022670

# **Special Features**

- High CRI chip LEDs paired with ½ stop soft diffusion panel
- Bi-Color adjustable from 3200K-5600K
- Beam angle of 110°
- Baby 5/8" / Junior 1 1/8" combo pin adapter with right angle receiver hole
- Strong steel tension knobs for locking the light into place
- Single Knob Control for adjusting Color & Brightness
- New LED Readout Screen gives precise adjustments
- Battery-Powered by two included Sony Style "L" Series Batteries
- Included Barn Doors with Intensifiers



## **Recommended For**

- Studio Lighting
- Field Lighting



www.facebook.com/ikanseeit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com

# MSB8-5PT-KIT

# Features you need, Prices you want.

#### **Constant Color & Brightness**

The high CRI LED chips and the ½ stop soft diffusion panel output a strong, bright, and diffused light. The soft light's bi-color adjustability ranges from 3200K-5600K and works well with any lighting production. The Mylo Soft's wide beam angle provides a large amount of soft light all on its own.

#### 110° Angle

The 110° wide beam angle provides a large amount of soft light all on its own.

#### **Combo Pin Adapter**

The Baby 5/8" and Junior 1 1/8" combo pin has a right angle receiver hole so you can quickly and easily attach it to any grip stand.

#### **Steel Tension Knobs**

The new, stronger steel tension knobs securely lock the light in place at any angle.

#### **Durability & Single Knob Control**

The heavy duty metal chassis with raised corners enables you to use the light in any shooting environment without risking damage. A single knob control makes it easy to adjust the light's brightness and color temperature with a few simple clicks.

#### **Battery Options & LED Readout**

This incredible package includes an AC power supply and two Sony "L" batteries for DC power. The new LED readout is brighter and provides a quick reference to the light output with precise measurements.

#### What's Included

2 x Light Bag

2 x Light Stand Bag

5 x Barn Doors

5 x Compact Light Stands

5 x Dual Battery Charger

5 x MSB8 Light Fixture

5 x Power Supply with Cable

5 x Yoke

10 x Sony "L" Series Style Batteries

| MSB8 Fixture Specifications |  |
|-----------------------------|--|
| Battery Type                | Sony "L" Series Style Batteries  |
| Beam Angle                  | 110°   |
| Build Material              | Heavy Duty Metal Construction  |
| Cooling System              | Passive Cooling  |
| Dimming                     | Knob Control   |
| Fixture Size                | 19 x 13 x 3.5 in.  |
| Fixture Weight              | 8 lbs  |
| Head Type                   | Bi-Color 3200K-5600K   |
| Power Supply                | Input: 100-240VAC<br>Output: 12 VDC@5.0A   |
| Yoke                        | Baby <sup>5</sup> / <sub>8</sub> " - Junior 1- <sup>1</sup> / <sub>8</sub> " Combo Pin |

| Shipping Specifications   |                  |  |
|---------------------------|------------------|--|
| Shipping Dimensions Box 1 | 24 x 22 x 18 in. |  |
| Shipping Dimensions Box 2 | 24 x 22 x 18 in. |  |
| Shipping Weight           | 98 lbs           |  |

#### **Optional Accessories**

CP-STND-V3 Compact Light Stand Version 3
HD-STND-V2 Heavy Duty Light Stand
KCP-703 Stage Clamp w/ 16mm Stud
ROLLR-STND10 2-Stage Roller Stand 10 ft 6in.

SW-04 Safety Wire PWRGP-01 Power Grip





