

OBM-U170

17.3" 4K Support HDR LCD Professional Monitor

ONE SHEET

Overview

Ikan and Postium team up to bring the most feature-rich line of 4K production monitors. The OBM series offers full 4K support up to 4096x2160 at 60p signals and features 12G-SDI single link and HDMI 2.0 inputs.

In addition to multiple input support, the OBM series boasts color accuracy and panel uniformity that are essential for color critical applications. The monitors support side-by-side color space and gamma comparison as well as full 3D-LUT support.

With the OBM series of monitors, Ikan and Postium have prioritized quality and compatibility to offer the most complete and versatile 4K monitors.



OBM-U170 | 17.3" 4K Support HDR LCD Professional Monitor | UPC Code: 847983021079

Special Features

- 1920 x 1080 10-Bit LCD Panel
- 12G-SDI Single Link & Quad Link 4K, HDMI 2.0
- HDR Support
- 3D LUT, Waveform, Vectorscope, Color Space & Gamma Comparison
- Ultra HD & Full DCI 4K Support

Recommended For

- Film Makers
- Color Graders
- Video Editors
- Broadcast



www.facebook.com/ikanseit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

ikan

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com

OBM-U170

Features you need, Prices you want.

Maximum Versatility

The OBM Series of monitors supports all the multiple 4K inputs such as HDMI 2.0, 12G-SDI, Dual 3G-SDI as well as support for 4K Quad Link 2 Sample Interleave and 4K Quad Link Square Division Signals. In addition, the monitors also include the SFP interface which allows the use of the SFP modules that fit any possible broadcast applications. The OBM Series of monitors can support up to 3840x2160 and 4096x2160 60p.

4K Waveform & Vectorscope

The OBM monitors feature real-time high resolution Waveform and Vector Scopes. Waveform Wide mode is supported and both the waveform and the vector scope can be displayed simultaneously

Wide Color Space & 3D-LUT Support

The OBM Series of Monitors features support for wide color gamuts. Different color spaces can be selected such as DCI-P3, ITU-R BT.2020, ITU-R BT.709, SMPTE-C, EBU, and the display's native color space. 3D-LUT support is also available, giving you the ability to load your own custom 3D-LUTs or choose from the built-in camera LOG LUTs. B) The OBM monitors have a unique feature that allows you to view two different color spaces or gammas side by side. The viewable areas can then be adjusted by wiping left or right.

Focus Assist & Zebra

The monitors also are equipped with features that help you get the right shot every time. For example, the Focus Assist highlights the edges of what is in focus in red. You also have the ability to adjust the sensitivity and color of the outline and whether you want the image in monochrome or color. The Zebra function is also available and will let you know what parts of the video are overexposed by overlaying a zebra pattern over them.

Adjustable Gamma

The gamma value can be adjusted from 1.0 to 3.0 so you are able to monitor the dark areas and the light areas of the image. Any footage captured in either light or dark environments can be monitored and analyzed.

Specifications

Size	17.3 in.
Resolution	1920 x 1080
Pixel Pitch	0.199mm
Color	10-Bit
Viewing Angle	178 (H) 179 (V)
Luminance of White	350 cd/m2
Contrast	1000:1
Back Light	LED
Display Area	(H x V) 381.9 x 214.8mm
Power Requirements	AC100-230V (50/60Hz)
Power Consumption	TBD
Operating Temperature	0°C ~ 40°C (32° F~104° F)
Operating Humidity	20%~80% RH
Weight	11 lbs
Dimensions	16.2 x 12.8 x 3.3 in. (with stand)

Shipping Specifications

Shipping Dimensions	21 x 18 x 10 in.
Shipping Weight	21 lbs

What's Included

- 1 x Manual
- 1 x Power Cord
- 1 x OBM-U170 Monitor
- 1 x Table Stand (*Attached*)

Optional Accessories

- AB101** Anton/Bauer Power Tap Cable with Coaxial
- PBK-A-X** Pro Battery Adapter Kit for Anton Bauer with XLR P-Tap
- PBK-S-X** Pro Battery Adapter Kit for V-Mount with XLR P-Tap
- Rack Mount Kit
- Wall Bracket
- Carrying Case

