

Remote Air 2 Dual Channel WLC (PD Movie)

ONE SHEET

Overview

The Remote Air 2 wireless follow focus is not just a new generation of the Remote Air--it's a new experience. The Remote Air 2 perfectly combines the receiver into the lens motor, reducing the weight by 200g. Imported from Germany, the brushless motor is impeccable and can drive various professional camera lenses such as the Angenieux/Arri Ultra/Cooke.



PD2-N | Remote Air 2 Dual Channel WLC (PD Movie) | UPC Code: 847983019557

Special Features

kan

- Two German engineered high precision lightweight, thin, and quiet motors compatible with 19 or 15mm rods
- High torque motors capable of operating all types of lenses from still photography to high end cine lenses
- 360° Hand Control Unit Knob with a 7200 resolution that is 13.4 times better than the original Remote Air
- Accurate OLED Screen displays channel info, signal strength, battery life, and voltage
- Communicates through a 20 channel 2.4 GHz wireless protocol, and has a signal transmission distance of 100m

Recommended For

- 1st AC's (Focus Puller)
- Camera Operators
- Cinematographers



www.ikancorp.com 1.713.272.8822 sales@ikancorp.com

PD2-N

Features you need, Prices you want.

Lighter, Stronger, Better

Two German engineered high precision lightweight, thin, and quiet motors compatible with 19mm or 15mm rods.

Highly Capable

High torque motors capable of operating all types of lenses from still photography to high end cine lenses.

Improved Precision

360° Hand control unit with a 7200 resolution that is 13.4 times better than the original Remote Air!

Accurate OLED Display Screen

The accurate OLED screen displays channel info, signal strength, battery life, and voltage.

Wireless 2.4 GHz Signal

Communicates through a 20 channel 2.4 GHz wireless protocol, & has a signal transmission distance of 100m.

What's Included

- 1 x Remote Air 2 Dual Channel Hand Control Unit
- 1 x Remote Air Pro Receiver Motor
- 1 x Remote Air Slave Motor
- 2 x 0.8 Pitch Gears (Pre-Assembled)
- 1 x 19m Rod Clamps (Pre-Assembled)
- 1 x 19mm 10 15mm Adapter Ring
- 1 x 4-Pin LEMO to Standard USB Cable
- 1 x 6-Pin LEMO to D-Tap Power Cable
- 1 x 6-Pin LEMO to 6-Pin LEMO Daisy Chain Cable
- 1 x Antenna (Long)
- 2 x Antenna (Short)
- 3 x Glow-in-the-Dark Marking Disks
- 1 x USB Power Adapter
- 1 x Travel Hard Case
- 1 x Remote Air 2 Product Manual
- 1 x PD Movie Lanyard

ikan

Remote Air 2 Dual Channel Hand Control Unit Specifications		
Weight	1.05 lbs	
Dimensions	7.95 x 2.44 x 2.2 in	
Remote Air Pro Receiver Motor Specifications		
Weight	0.4 lbs	
Voltage	12-18V	
Remote Air Pro Slave Motor Specifications		

0.37 lbs

0.8 Pitch Gears Specifications		
Teeth	40	
Face	6 mm	
Quantity	2	
4-Pin LEMO to Standard USB Cable Specifications		
Length	34 In.	
6-Pin LEMO to D-Tap Power Cable Specifications		
Length	24 ln.	
6-Pin LEMO to 6-Pin LEMO Daisy Chain Cable Specifications		
Length	9.5 ln.	
Chinning Crocifications		

Snipping Specifications		
Shipping Dimensions	15 x 10.4 x 3.5 ln.	
Shipping Weight	6 lbs	

Optional Accessories

P P

Ρ

Ρ

P P P

Weight

D-DISK-GLO	Glow-in-the-Dark Marking Disk
D3-ANT	Remote Air Pro Antenna
D3-CHR	Remote Air Pro USB Charger
D3-M	Remote Air Pro Slave Motor
D3-MC	Remote Air Pro Motor Cable
D3-MC-22	Remote Air Pro Motor Extension Cable 22 In.
D3-R	Remote Air Pro Receiver Motor
D3-USB	Remote Air Pro USB Charging Cable

