

ONE SHEET

Overview

The fixture's slim profile allows you to place the light in numerous shooting environments. Edge-lit technology and no exposed LEDs produce a broad wash of soft accent light.

The daylight 5600K color temp with a 95CRI means you can rely on the color choice. Pre-attached gel clips make for quick and easy color changes.

Aluminum housing creates a rigid but lightweight fixture.

Three different battery plates - one each for Canon,

Panasonic and Sony - expand your capture options. A digital readout on the back makes it easy to check battery power and brightness levels



PL103 | Piatto 10" x 3" Accent Light | UPC Code: 847983012459

Special Features

- The slim profile of the light allows for it to be placed anywhere.
- The 10" x 3" accent light allows for softer source.
- Constructed of a light weight aluminum
- 5600K color temperature with a 95CRI
- Multiple battery plates included (Canon, Panasonic, Sony)
- Digital readout gives battery life indicator as well as brightness level.
- Pre attached gel clips for making attachment of gel and snap.
- Includes LM102 stand mount for attachment to any stand.



Recommended For

- Studio Lighting
- Small Product Photography
- Interviews
- Fill Lights
- Portraits



www.facebook.com/ikanseeit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

Features you need, Prices you want.

Slim Profile

With such a sleek, slim profile, the Piatto series allows you the convenience of being able to be placed anywhere. Tedious setup and complicated clean up times become a thing of the past when using this series.



Lightweight aluminum frame adds to the elegance of these lights.

LM102 Stand Mount

The Piatto family includes a LM102 (5/8" Size Pin) stand mount for easy attachment to any stand.



Digital Readout

An easy-to-view digital readout indicates battery life as you shoot, as well as a brightness level for the simplest of adjustments.

What's Included

- 1 x PL103 Light
- 1 x LM102
- 1 x 12V 2A Replacement Power Supply AC-12V-2A-US
- 1 x Canon 900 Series Battery Plate for BP2-C
- 1 x Panasonic D54 Battery Plate for BP2-P
- 1 x Sony L Series Battery Plate for BP2-S

| Specifications | |
|---------------------|---------------------------|
| Build Material | Aluminum |
| Control | Local Knob Control |
| Focusing | N/A |
| Dimming | 10-100% |
| Head Type | Daylight (5600K) |
| Yoke | N/A |
| Lens | Edge Light Prism |
| Beam Angle | 120° |
| Light Source | 300 0.06 Watt LED @ 5600K |
| Power Supply | 12v @ 2 Amps |
| Rating | 120 volts AC, 50-60hrz |
| Cooling System | Passive Heat Sync |
| Fixture Size | 10" x 1" x 3" |
| Fixture Weight | 1.3 lbs |
| Shipping Dimensions | 2.5" x 9.5" x 18.75" |
| Shipping Weight | 3.2 lbs |

Multiple Battery Plates

Each member of the Piatto family comes with multiple battery plates (Canon, Panasonic, & Sony).

Optional Accessories

IBS-970 Sony L-Series NP-F970 Compatible Battery

IBS-1170 Sony "L" Series Compatible Ultra High Capacity Battery

IBC-950G Canon Compatible Battery

IBC-988 Canon "900" Series Ultra High Capacity Battery

IBP-D54 Panasonic Compatible Battery

IBP-D88 Panasonic "D54" Ultra High Capacity Battery

HD-STND Heavy Duty Light Stand

AB-101 Anton/Bauer Power Tap Cable with Coaxial

Photometrics





