

Recordable RM-072S



- HDMI-to-SDI Loop-through Converter
- Supporting 3G-SDI (Level A/B)
- Support for PC-playable file format(mov)
- Battery Level Indicator
- Waveform/Verctor scope
- Closed Caption(CEA-608/708)
- Time Code(Except 3G Level B)
- UMD/IMD Mode
- R/G/B and White Internal Patterns Display
- Zero/Under/Over Scan, Blue/Mono
- 1280*720/30p, 25p HD Recording with H.264 Video Codec
- H/V Delay
- Auto Recording with GPIO
- Various Recordable Input
- Thumbnail File List
- Focus Assistance
- Compatible to various DSLR Output
- Various Play Mode
- 8~16ch Audio Level Meter
- Various Markers
- Exposure Range Check
- AFD & V-CHIP(SDI Only)
- Pixel-to-Pixel View
- 2ch Audio Recording with MPEG-2 AAC Codec

RM-072S

RM-072S is a H.264 recordable monitor with SDI and HDMI inputs. Users can record the input signal on the screen and play it back instantly for review on a SD card. RM-072 is available for HDMI only.

LCD			
Size	7.0"	Luminance of White	400 cd/m ²
Resolution	1024 x 600	Contrast	900 : 1
Pixel Pitch	0.15 x 0.15 mm	Back Light	LED
Color	8bit	Display Area (H x V)	153.6 x 90.0 mm
Viewing Angle	160(H), 160(V)		
Input			
3G/HD/SD-SDI	HDMI(with HDCP v.1.1) 19pin Female		
Output			
Selectable SDI-1/2 Loop-through or HDMI conversion Out			
Input Signal Format			
SMPTE 425M AB	SMPTE 274M/292M	SMPTE 296M	SMPTE 260M
SMPTE 125M/259M	2K, SMPTE 428M	ITU R-BT.656	HDMI
Audio In / Out			
1 x Headphone Jack In	1 x Headphone Jack Out	1 x Speaker Out	
Recording & Play			
Recordable Input	SDI, HDMI		
Codec	H.264 (Video), AAC(Audio)		
Video Bit Rate	4Mbps		
External Memory	Max 32GB (Class 4 or higher SDHC Card)		
Max Record Size	2GB per file (About One Hour)		
Recording Format	1280x720 / 30p, 25p		
File Format	mov		
Play Mode	Play, 2x/8x/32x FF/REW, 1/2x/1/8x/1/32x Slow, 2x/8x/32x Frame FF/REW		

* Optional accessories available