

RS-F200

Red Star 6" LED Tungsten Fresnel 200 Watt Light

ONE SHEET

Overview

The Red Star 6" Fresnel 200-watt light is designed and built for professional photographers, videographers and cinematographers who want high quality at an affordable price.

The 3200K Tungsten Fresnel delivers field-tested reliability, solid construction, and all the features required for professional performance. The RS-F200 features include a six-inch Fresnel lens with a spot-to-flood focusing knob and quiet active cooling system that deliver reliable, consistent performance.

The light is made of solid aluminum and has an energy-efficient LED with high output and excellent color rendering index (CRI). The Red Star has local built-in dimming as well as a digital readout for assigning the light to a DMX channel. The ultra-quiet active cooling fan pulls heat from the fixture. The 4-leaf barn doors cut and shape the light and can be folded flat for transportation.



RS-F200 | Red Star 6" Tungsten Fresnel 200 Watt Light | UPC Code: 847983014583

Special Features

- 6" Fresnel Lens with Spot Flood Focusing Knob
- Quiet Active Cooling System
- 512 DMX In and Out, Channel Selectors with Digital Readout
- Solid Aluminum Construction
- 4 Way Barn Doors Included (4 Leaf)
- Local Dimming Knob

Recommended For

- Studio Lighting
- Interviews

ikan

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com



www.facebook.com/ikanseit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

RS-F200

Features you need, Prices you want.

Spot to Flood Lighting

Knob that focuses the light from spot to flood.

Quiet Active Cooling System

Ultra-quiet cooling fan for pulling heat from the fixture.

512 DMX Channel Selectors

Digital readout for assigning the DMX channel of your choice.

4-Way Barn Doors

Black four (4) leaf barn doors for cutting and shaping the light.

Local Dimming Knob

Local dimming for controlling the brightness of the lights.

What's Included

- 1 x 200 Watt Light Fixture
- 1 x 10ft Power Cable
- 1 x Barn Doors
- 1 x Yoke
- 2 x Yoke Screws
- 4 x Yoke Washers



Accessories

- KCP-703 Stage Clamp w/ 16mm Stud
- SW-04 Safety Wire
- MK350 Spectrometer from UPRtek
- IDX-1204 12 Channel DMX Console
- IDX-096 96 Channel DMX Console

Specifications

Beam Angle	15-50 Degree
Build Material	Aluminum
Control	DMX512 IN/OUT - Toggle Button DMX Control
Cooling System	Active Cooling Fan
CRI	96
Dimming	Flicker-Free Dimming, Onboard Dimming Knob, 100-0% DMX Dimmer (Minimal Color Shift)
Fixture Size	13 x 10 x 12 In.
Fixture Weight	20 lbs
Focusing	Rotating Rear Knob
Foot Candles (Flood)	5ft-386 FC / 10ft-118 FC / 15ft-57 FC
Foot Candles (Spot)	5ft-1812 FC / 10ft-731 FC / 15ft-330 FC
Head Type	Tungsten (3200K)
Lens	6 In. Glass Fresnel
Light Source	1 x 200 watt Warm LED 3200K
LUX (Flood)	1.5m-4154 LUX / 3m-1272 LUX / 4.5m-615 LUX
LUX (Spot)	1.5m-19496 LUX / 3m-870 LUX / 4.5m-3553 LUX
Power Supply	6 Ft. Power Cable
Rating	120 Volts AC / 50-60Hz / 150 Watts 63-14 amps
Shipping Dimensions	18 x 15 x 17 In.
Shipping Weight	24 lbs
Yoke	Cast Aluminum w/ 1 1/8" Pin

Photometrics



ikan

Houston, Texas

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com